

Inform Rill Records at 1918

Optical Fiber Technology

being attack shalls address where

- Laborer felding hereiterter
- The second second
- President bankation but a service and
- Rouge allocation and a design
- Wand and F. Mr group of going for
- Aurile and the interpret frightened inter-
- Induced reportance I when you descent
- An adaptation from the second second



State in succession.

houseboard



Home (https://www.elsevier.com/) - Journals (https://www.elsevier.com/catalog?producttyp...

- Optical Fiber Technology (https://www.journals.elsevie...
- Editorial Board (https://www.journals.elsevier.com:¢¢y/optical-fiber-technology/editorial-board)

Submit Your Paper (https://www.editorialmanager.com/oft/default.aspx) Supports Open Access (https://www.elsevier.com/journals/optical-fiber-technology/1068µ200/open-access-options)

SEARCH

MENU

View Articles (https://www.sciencedirect.com/science/journal/1068µ200)

Guide for Authors Abstracting/Indexing (http://www.elsevier.com/journals/optical-fiber-technology/ 1068-µ200/abstracting-indexing)

Track Your Paper Order Journal Journal Metrics CiteScore: 3.0 Impact Factor: 2.212 µ-Year Impact Factor: 1.871 Source Normalized Impact per Paper (SNIP): 0.970 SCImago Journal Rank (SJR): 0.555 View More on Journal Insights

Your Research Data

Share your research data (https://www.elsevier.com/authors/author-resources/research-data) Data in Brief co-submission (https://www.elsevier.com/authors/author-resources/research-data/dataarticles/DIB-co-submission) MethodsX co-submission (https://www.elsevier.com/authors/author-resources/research-data/materialsand-methods/mex-co-submission)

Related Links

Author Stats Researcher Academy Author Resources (https://www.elsevier.com/authors/author-resources) Try out personalized alert features

Related Publications

Physics Open (https://www.elsevier.com/locate/inca/7¢7¢µy) Results in Physics (https://www.elsevier.com/locate/inca/72µQQ6)

Optical Fiber Technology - Editorial Board

Editor-in-Chief

S. Wabnitz (https://www.journals.elsevier.com:¢¢3/optical- fiber-technology/editorial-board/s-wabnitz)

Elettronica e Telecomunicazioni,Dipartimento di Ingegneria dell'Informazione,Sapienza Università di Roma, Via Eudossiana 18, 0018¢, Rome, Italy

Deputy Editor

G. Brambilla University of Southampton Optoelectronics Research Centre, University Road, SO1y 1BJ, Southampton, United Kingdom

Associate Editors

A. Cucinotta University of Parma Department of Engineering and Architecture, Parma, Italy

F. Li

Sun Yat-Sen University School of Electronics and Information Technology, Guangzhou, China C.A.F. Marques (https://www.journals.elsevier.com:¢¢3/optical-fiber-technology/ editorial-board/caf-marques) University of Aveiro, Department of Physics, Aveiro, Portugal

K. Nakajima NTT Access Network Service Systems Laboratories, Ibaraki, Japan

Anuj K. Sharma (https://www.journals.elsevier.com:¢¢3/optical-fiber-technology/ editorial-board/anuj-k-sharma) National Institute of Technology Delhi, India.

M. Soto (https://www.journals.elsevier.com:¢¢3/optical-fiber-technology/editorialboard/m-soto) Federico Santa Maria Technical University Department of Electronic Engineering, Valparaíso, Chile

A. Sysoliatin (https://www.journals.elsevier.com:¢¢3/optical-fiber-technology/editorialboard/a-sysoliatin) Russian Academy of Sciences, Moscow, Russia

A. Tonello Limoges University, France L. Yi

Shanghai Jiao Tong University School of Electronic Information and Electrical Engineering, Shanghai, China

1

Advisory Board

A. Barthelemy Limoges University, Limoges, France

M. Chbat Nokia Solutions and Networks Oy, ESPOO, Finland

J.-M. Delavaux Keopsys Inc, Pittstown, United States

B. Desthieux Nokia Networks Belgium, Antwerpen, Belgium

M.F. Ferreira University of Aveiro, Aveiro, Portugal

R. Minasian The University of Sydney, Sydney, Australia

D. Richardson University of Southampton, Southampton, United Kingdom

Founding Editor

E. Desurvire Nokia Networks France Villarceaux, Nozay, France

Honorary Editors

M. Nakazawa Tohoku University Research Institute of Electrical Communication, Katahira 2-1-1, Aobaku, ç8o-85yy, Sendai, Japan

E. Snitzer Rutgers University Fiber Optics Materials Research Program, 6oy Taylor Road, Piscataway, New Jersey, NJ 0885¢-8065, United States



Optical Fiber Technology

Supports open access

Articles in press	Latest issue	Article collections	All issues	Submit your article 🕫

Search in this journal

Volume 52 November 2019

Previous vol/issue

Next vol/issue >

Receive an update when the latest issues in this journal are published

Sign in to set up alerts

Full text access Editorial Board Article 102047

🕁 Download PDF

Full text access Publisher's Note Article 102050

▲ Download PDF ■

Research Articles

Research article O Abstract only Hollow core photonic crystal fiber for chemical identification in terahertz regime Md. Ahasan Habib, Md. Shamim Anower, Lway Faisal Abdulrazak, Md. Selim Reza Article 101933

▲ Purchase PDF Article preview ∨

Research article O Abstract only

Generation of orbital angular momentum mode using a single cylindrical vector mode based on mode selective coupler

Hongwei Zhang, Baiwei Mao, Ya Han, Kang Yang, ... Yange Liu Article 101934

▲ Purchase PDF Article preview ∨

Research article O Abstract only Gamma radiation impact on the fiber optic acetone gas sensing behaviour of magnesium tetraborate R. Mohandoss, B. Renganathan, O. Annalakshmi, A.R. Ganesan Article 101935

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only

The surgical ablation on soft tissues using Ho:YAG laser with deviated beam fiber Nurul Syahirah Aziz Jaafar, Kok-Sing Lim, Muhammad Khairol Annuar Zaini, Harith Ahmad, ... Zulkifli Md. Zainuddin Article 101937

▲ Purchase PDF Article preview ∨

Research article O Abstract only Wavelength, repetition rate, and pulse width tunable high average power narrow linewidth 1.5 µm fiber amplifier Yulong Cui, Ni Tang, Zhiyue Zhou, Zhixian Li, Zefeng Wang Article 101938

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only

DFTs-OFDM based quantum noise stream cipher system Xiaokun Yang, Jie Zhang, Yajie Li, Yongli Zhao, ... Huibin Zhang Article 101939

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only

(Network-service value)-based admission decision mechanism for ONU's virtual access under distributed control in virtual passive optical network Xingdi Wang, Chaoqin Gan, Yuanyuan Chen, Liya Tong Article 101940

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only

Tailor-made photonic crystal fiber sensor for the selective detection of formaldehyde and benzene

Jinxiao Wang, Jianfeng Yang, Dening Zou, Jun Yang, ... Ruihu Wang Article 101941

▲ Purchase PDF Article preview ∨

Research article $\, {\rm O} \,$ Abstract only

340-Gb/s PolSK-DP-DQPSK optical orthogonal modulation format with coherent direct detection for high capacity WDM optical network Sukhbir Singh, Surinder Singh, Quang Minh Ngo, Amin Malek Mohammadi Article 101936

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only

Hybrid MMW-over fiber/OFDM-FSO transmission system based on doublet lens scheme and POLMUX technique

Khaleda Mallick, Paulomi Mandal, Gour Chandra Mandal, Rahul Mukherjee, ... Ardhendu Sekhar Patra Article 101942

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only

Nonlinear distortion estimation in dual-carrier PM-QPSK signals for uncompensated fiber links Abdullah S. Karar Article 101943

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only

Scale factor calibration and dynamic angle measurement method based on selfcollimator and fiber optic gyroscope Jiapeng Mou, Tengchao Huang, Guangyao Ying, Shuangliang Che, Xiaowu Shu Article 101945

▲ Purchase PDF Article preview ∨

Research article O Abstract only Suspended graded-index porous core POF for ultra-flat near-zero dispersion terahertz transmission Sen Mei, Depeng Kong, Lili Wang, Tian Ma, ... Yani Zhang Article 101946

 $rightarrow Purchase PDF Article preview <math>\checkmark$

Research article O Abstract only

Dedicated and broadcasting downstream transmission with energy-efficient and latencyaware ONU interconnection in WDM-PON for smart cities Amit Kumar Garg, Vijay Janyani, Ghanshyam Singh, Tawfik Ismail, Hossam Selmy Article 101949

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only

Flat-gain and wide-band partial double-pass erbium co-doped fiber amplifier with

hybrid gain medium

Aya A. Almukhtar, Alabbas A. Al-Azzawi, B.A. Ahmad, X.S. Cheng, ... S.W. Harun Article 101952

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only

Optical Fiber Technology | Vol 52, November 2019 | ScienceDirect.com

Arc-discharge-induced off-axis spiral long period fiber gratings and their sensing characteristics Yin Liu, Hongchang Deng, Libo Yuan Article 101950 ★ Purchase PDF Article preview ✓

Research article $\, \circ \,$ Abstract only

Thermally induced emission from hydroxyl groups in fused silica optical fibers Li Yu, Daniel Homa, Paul Ohodnicki, Michael Buric, ... Anbo Wang Article 101951

 $rightarrow Purchase PDF Article preview <math>\checkmark$

Research article O Abstract only

Interfacial strain transfer in embedded optical fibre sensors with eye-shaped interface Rong-mei Liu, Lujia Zhu Article 101954

🗠 Purchase PDF 🛛 Article preview 🗸

Research article O Abstract only

Bending characteristic of large-mode-area fibers with uniaxial crystal material cladding Caijian Xie, Tigang Ning, Li Pei, Shaoshuo Ma, ... Shanglin Hou Article 101953

▲ Purchase PDF Article preview ∨

Research article O Abstract only

Two-dimensional microbend sensor based on the 2-core fiber with hump-shaped taper

fiber structure

Lu Wang, Yanxin Zhang, Weigang Zhang, Lingxin Kong, ... Tieyi Yan Article 101948

▲ Purchase PDF Article preview ∨

Research article O Abstract only

Mode-locking soliton generation using platinum in figure-8 configuration N.A. Awang, A.N. Azmi, Y.R. Yuzaile, N.U.H.H. Zalkepali, Z. Zakaria Article 101956

▲ Purchase PDF Article preview
✓

Research article $\, \circ \,$ Abstract only

Optical network unit placement in Fiber-Wireless (FiWi) access network by Whale Optimization Algorithm Puja Singh, Shashi Prakash Article 101965

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only

An in-fiber integrated multifunctional mode converter Gongdai Chen, Hongchang Deng, Shitai Yang, Chao Ma, Libo Yuan Article 101961

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only A highly selective LSPR biosensor for the detection of taurine realized on optical fiber substrate and gold nanoparticles Priyanka Sharma, Vivek Semwal, Banshi D. Gupta Article 101962

▲ Purchase PDF Article preview ∨

Research article O Abstract only

Machine learning based dynamic load balancing DWBA scheme for TWDM PON Rizwan Aslam Butt, M. Faheem, Asad Arfeen, M. Waqar Ashraf, Mehwish Jawed Article 101964

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only

Use of C-band erbium gain-medium and compound-fiber-ring design for singlelongitudinal-mode fiber laser with 84-nm achievable tunability Yue-Ru Xie, Chien-Ming Luo, Chien-Hung Yeh Article 101974

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only Tensile strength and failure behavior of bare single mode fibers Zhangwei Ma, Zhifeng Wang, Huanhuan Liu, Fufei Pang, ... Tingyun Wang Article 101966 ▲ Purchase PDF Article preview ∨

Research article O Abstract only Passive Q-switching using Lead Sulfide suspension as a saturable absorber in 1.5 μm region Hiba Hassan, Ali A. Salman, Mohammed A. Munshid, Abdulhadi Al-Janabi Article 101969

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only

Macrobending SMS fiber-optic anemometer and flow sensor

Jesse W. Costa, Marcos A.R. Franco, Valdir A. Serrão, Cristiano M.B. Cordeiro, Maria T.R. Giraldi Article 101981

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only

Optimization of sensing performance factor (γ) based on microfiber-coupled ZnO

nanorods humidity scheme

Mohd Hafiz Jali, Hazli Rafis Abdul Rahim, Haziezol Helmi Mohd Yusof, Md Ashadi Md Johari, ... Moh Yasin

Article 101983

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only Practical research on photonic crystal fiber micro-strain sensor Ronghua Fan, Lianqin Li, Yueyang Zhuo, Xiang Lv, ... Baojin Peng Article 101959

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only

Fiber optic sensor using ZnO for detection of adulterated tequila with methanol Jorge Isaac Necochea-Chamorro, Roberto Carlos Carrillo-Torres, Raúl Sánchez-Zeferino, Mario Enrique Álvarez-Ramos Article 101982

▲ Purchase PDF Article preview ∨

IDF: Intelligent Defragmentation Method in Elastic Optical Networks based on decision making algorithms Ali Athari Beyragh, Akbar Ghaffarpour Rahbar, Mohsen Nickray Article 101978

🖞 Purchase PDF 🛛 Article preview 🗸

Research article O Abstract only

Fiber bundle sensor for detection of formaldehyde concentration in fish M. Yasin, N. Irawati, A.H. Zaidan, Kismiyati, ... A.M. Perego Article 101984

ightarrow Purchase PDF Article preview \checkmark

Research article O Abstract only

Performance optimization of decoy-state BB84- and MDI- QKD protocol and their key integrating application strategy for power dispatching Yonghong Ma, Lichen Yi, Guochen Wei, Xiongwen Zhao Article 101944

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only

Performance-enhanced optical fiber hydrogen sensors based on WO₃-Pd₂Pt-Pt composite film with controlled optical heating Gaopeng Wang, Yuhuan Qin, Jixiang Dai, Shiwen Yang, ... Minghong Yang Article 101979

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only Curvature sensor based on SMF taper in fiber loop ring down system Wen Wei Chen, Chun Liu Zhao, Zhao Kun Wang, Bang Ning Mao Article 101977

 $rightarrow Purchase PDF Article preview <math>\checkmark$

Research article O Abstract only

Comprehensive investigation of evanescent wave optical fiber refractive index sensor coated with ZnO nanoparticles Zahra Samavati, Alireza Samavati, Ahmad Fauzi Ismail, Mohd Hafiz Dzarfan Othman, Mukhlis A. Rahman

Article 101976

▲ Purchase PDF Article preview ∨

Research article O Abstract only Analysis of nano-creep deformation of epoxy adhesive in optical fiber connector for long-term reliability prediction Kota Shikama, Atsushi Aratake, Yasuhiro Koike Article 101975

▲ Purchase PDF Article preview ∨

Research article O Abstract only Intelligent detection technology for leakage bag of baghouse based on distributed optical fiber sensor Xu'an Liu, Jun Li, Bo Shi, Guoshen Ding, ... Zhirong Zhang Article 101947

▲ Purchase PDF Article preview ∨

Research article O Abstract only

Intentional spectrum waste to reduce blocking probability in space division multiplexed elastic optical networks Amin Ghadesi, Akbar Ghaffarpour Rahbar, Mohsen Yaghubi-Namaad, Asiyeh Abi Article 101968

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only

Design of all optical contention detection circuit based on HNLF at the data rate of 120 Gbps Surinder Singh, Dilbag Singh, Vishal Sharma, Sukhbir Singh, Quang Minh Ngo Article 101958

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only

Integration system of photon-assisted W-band millimeter wave wireless communication and free space optical communication based on OFDM signal transmission Long Chen, Jiabin Luo, Zhijun Tang, Zaifang Xi Article 101973

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only

Environmentally-stable 50-fs pulse generation directly from an Er:fiber oscillator Jiaqi Zhou, Weiwei Pan, Xiaohu Fu, Lei Zhang, Yan Feng Article 101963

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only

Switchable erbium-doped fiber laser (EDFL) using non-adiabatic microfiber M.A.M. Salim, Norazida Ali, Saaidal R. Azzuhri, M.I.M. Abdul Khudus, ... I.S. Amiri Article 101967

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only

Transmission of 100 Gbit/s PAM-8 signal over 40-km SMF with 10 GHz DML in O-band Wei Wang, Zibin Li, Dongdong Zou, Hui Zhou, ... Fan Li Article 101957

▲ Purchase PDF Article preview ∨

Research article O Abstract only

Two-core fiber based mode coupler for single-mode excitation in a two-mode fiber for quasi-single-mode operation Thomas Joseph, Joseph John

Article 101970

🗠 Purchase PDF 🛛 Article preview 🗸

Research article O Abstract only

Multi-functional photonic crystal fiber splitter for the two communication bands Esam A.A. Hagras, Mohamed Farhat O. Hameed, A.M. Heikal, S.S.A. Obayya Article 101986

▲ Purchase PDF Article preview ∨

Research article O Abstract only

Event detection method comparison for distributed acoustic sensors using ϕ -OTDR Minjie Zhang, Yingchun Li, Jian Chen, Yingxiong Song, ... Min Wang Article 101980

▲ Purchase PDF Article preview ∨

Research article O Abstract only

Deep learning-assisted adaptive modulation level assignment for video communication over an elastic optical network Hamed Alizadeh Ghazijahani, Hadi Seyedarabi, Javad Musevi Niya, Ngai-Man Cheung Article 101987

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only

Wide-range temperature sensor based on enhanced up-conversion luminescence in Er^{3+}/Yb^{3+} co-doped Y_2O_3 crystal fiber Renjie Bao, Ni An, Linhua Ye, Li-Gang Wang Article 101989

▲ Purchase PDF Article preview ∨

Research article O Abstract only

Terahertz detection of toxic gas using a photonic crystal fiber

Jianyuan Qin, Bei Zhu, Yong Du, Zhanghua Han Article 101990

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only SOA/EDFA/RAMAN optical amplifier for DWDM systems at the edge of L & U wavelength bands Ajaybeer kaur, Manjit Singh Bhamrah, Ahmad Atieh Article 101971

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only

Utilizing polarization-multiplexing for free space optical communication transmission with security operation Chien-Hung Yeh, Yao-Jen Chang, Chi-Wai Chow, Wen-Piao Lin Article 101992

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only

A pre-split multi-flow RMSA algorithm in elastic optical networks Junling Yuan, Zhimin Xu, Ruijie Zhu, Qikun Zhang, ... Jing Zhang Article 101993

▲ Purchase PDF Article preview ∨

Research article O Abstract only Holmium oxide thin film as a saturable absorber for generating Q-switched and modelocked erbium-doped fiber lasers Ahmed Shakir Al-Hiti, M.F.A. Rahman, S.W. Harun, P. Yupapin, M. Yasin Article 101996

 $rightarrow Purchase PDF Article preview <math>\checkmark$

Special Section: Special issue on "Revival of Multimode Fiber Optics"

Research article O Abstract only Brightness enhancement with Raman fiber lasers and amplifiers using multi-mode or multi-clad fibers Yaakov Glick, Yariv Shamir, Yoav Sintov, Sharone Goldring, Shaul Pearl Article 101955

 \checkmark Purchase PDF Article preview \checkmark

Research article Open access Imaging through multimode fibers using deep learning: The effects of intensity versus holographic recording of the speckle pattern Eirini Kakkava, Babak Rahmani, Navid Borhani, Uğur Teğin, ... Demetri Psaltis Article 101985

🗠 Download PDF 🛛 Article preview 🗸

Research article O Abstract only Invited paper: Characterization of few mode fibers and devices Lars Grüner-Nielsen, Neethu Mariam Mathew, Karsten Rottwitt Article 101972

 \checkmark Purchase PDF Article preview \checkmark

Research article O Abstract only Numerical mode decomposition for multimode fiber: From multi-variable optimization to deep learning Yi An, Jun Li, Liangjin Huang, Lei Li, ... Pu Zhou Article 101960 ▲ Purchase PDF Article preview ∨

Research article O Abstract only

Femtosecond-pulse inscribed FBGs for mode selection in multimode fiber lasers Alexandr V. Dostovalov, Alexey A. Wolf, Mikhail I. Skvortsov, Sofia R. Abdullina, ... Sergey A. Babin Article 101988

▲ Purchase PDF Article preview ∨

Previous vol/issue

Next vol/issue >

ISSN: 1068-5200

Copyright © 2020 Elsevier Inc. All rights reserved

ELSEVIER

Remote access

About ScienceDirect

Shopping cart

Advertise

Contact and support

Terms and conditions

Privacy policy

We use cookies to help provide and enhance our service and tailor content and ads. By continuing you agree to the **use of cookies**. Copyright © 2020 Elsevier B.V. or its licensors or contributors. ScienceDirect ® is a registered trademark of Elsevier B.V. ScienceDirect ® is a registered trademark of Elsevier B.V.





Contents lists available at ScienceDirect

Optical Fiber Technology

journal homepage: www.elsevier.com/locate/yofte



Fiber bundle sensor for detection of formaldehyde concentration in fish

M. Yasin^{a,*}, N. Irawati^a, A.H. Zaidan^a, Kismiyati^b, <mark>A.T. Mukti^b</mark>, A. Soegianto^c, D.K.P. Rosalia^d, R.A. Wardani^d, M. Khasanah^e, H.J. Kbashi^f, A.M. Perego^{f,*}

^a Department of Physics, Faculty of Science and Technology, University of Airlangga, Surabaya 60115, Indonesia

^b Department of Fish Health Management and Aquaculture, Faculty of Fisheries and Marine, University of Airlangga, Surabaya 60115, Indonesia

^c Department of Biology, Faculty of Science and Technology, University of Airlangga, Surabaya 60115, Indonesia

^d Fisheries and Marine Biotechnology, Faculty of Fisheries and Marine, University of Airlangga, Surabaya, Indonesia

^f Aston Institute of Photonics Technologies, Aston University, Aston Triangle B4 7ET Birmingham, UK

ABSTRACT

We experimentally demonstrate an optical fiber bundle based sensor for measuring formaldehyde concentration in fish. We show that when contaminated fish samples are shined with red laser light with about 630 nm wavelength, the intensity of the backscattered radiation increases linearly with respect to the formaldehyde concentration. Our sensor has a simple architecture, it exhibits good sensitivity, linearity and stability and it has been tested for formaldehyde concentrations ranging from 3% to 21%. Our sensor allows non-destructive, on-site measurements and will have applications towards the development of all-optical cheap and portable sensors for detection of pollutants and toxic chemicals in the food industry and in the agriculture sector, being potentially suitable for measurements in the field.

1. Introduction

Detection of pollutants and of substances which are noxious for human health, both naturally present and surreptitiously added in the food production and supply chain, will be a major trend in optical sensing engineering in the present century. The demand for more sensitive, precise and selective sensors is motivated both by the scientific and technological challenge and by the increasingly higher standards in health and safety set by governmental policies for their citizens welfare. Especially in developing countries where quality and safety controls are currently looser, the risks of people contamination, with potentially deadly consequences, is higher and hence more efficient and practical techniques are required.

One of the current social problems related to food safety in developing countries (such as Malaysia, Indonesia, Thailand, Bangladesh to name just a few) is indeed the addition of formalin to the most various kinds of food including meat, fish and milk. Formalin is a solution of formaldehyde in water. Formaldehyde is a chemical substance tremendously noxious for human health being the cause of a variety of illnesses including different forms of cancer and leukemia [1,2]. It preserves the apparent look of food samples making them look healthy and fresh even when they are not any more so. For this reason, rogue traders use formalin to illegally sell rotten food, causing a two-fold damage to people: the eating of rotten food itself and the ingestion of the highly noxious formaldehyde. While sensing of formaldehyde in the gaseous state, released from some construction materials for instance, has been studied quite extensively both using electronics and photonics based sensing platforms [3–5], the research on sensing of formaldehyde in food is much less developed. In such research area, while chemical methods based on chromatography [6,7] and mass spectroscopy [8] are accurate, they require sample treatment and long time measurements which should be performed in dedicated labs; photonics, potentially opens room for cheaper and portable sensing platforms with applications for measurements in the field.

Besides works on opto-chemical sensing [9–11], some recent experiments have demonstrated the possibility of detecting formaldehyde and measuring its concentration in liquids exploiting the emission of fluorescence [12–14] or based on Raman spectroscopy, especially surface enhanced Raman scattering enabled by metallic nanoparticles [15–18]. In an alternative approach, attenuated total internal reflection in bent plastic optical fibers has been used to measure concentration of formaldehyde in milk [19].

We present here experimental results obtained with a fiber bundle sensor, about the optical non-destructive, on-site measurement of formaldehyde concentration in fish using a very simple detection scheme based on collecting the intensity of laser light reflected from the food sample, fish in our particular study, contaminated by formaldehyde.

* Corresponding authors. *E-mail addresses:* yasin@fst.unair.ac.id (M. Yasin), a.perego1@aston.ac.uk (A.M. Perego).

https://doi.org/10.1016/j.yofte.2019.101984

^e Department of Chemistry, Faculty of Science and Technology, University of Airlangga, Surabaya 60115, Indonesia

Received 21 June 2019; Received in revised form 11 July 2019; Accepted 19 July 2019 1068-5200/ © 2019 Elsevier Inc. All rights reserved.



Fig. 1. Experimental setup.

2. Experimental setup

We used a Helium-Neon laser emitting in the visible at 633 nm to illuminate a fish sample through a 2 ports fiber bundle probe; the intensity of the light reflected from the fish was collected through the second port of the fiber bundle probe and measured by a Newport SL-818 optical detector connected to a digital voltmeter. The fiber bundle probe was attached to a support with micrometric movement, which allowed to finely control the distance between the probe and the sample. A schematic of the experimental setup is shown in Fig. 1.

3. Results

We have tested our sensor on two different kinds of fish popular in Indonesia: the snapper and the gouramis fish.

For each kind of fish we have immersed one entire fish in formalin for 1 h and then measured the output voltage of the detector by varying the distance of the fiber bundle probe from the fish, from 0 to 1 mm in steps of 50 μ m. We have repeated the procedure for 8 different concentrations of formaldehyde in water ranging from 0% to 21% in steps of 3% (for each specie 8 different fish samples have been used, one for each formaldehyde concentration). We observed that the detector output voltage increased proportionally to the formaldehyde concentration due to an enhanced backscattering caused by formaldehyde.

As one could expect, the voltage response decreases instead with



Fig. 3. Linearity of the sensor: output voltage versus formaldehyde concentration at zero probe-sample displacement for both snapper and gouramis fish (see legend). Dots represent averages over 10 different realizations of the experiment, while error bars represent the corresponding standard deviations. Results of linear fits are reported close the respective data sets.



Fig. 2. The sensor output voltage is plotted versus the displacement between fiber bundle probe and fish sample for the snapper fish in (a) and for the gouramis fish in (b). Note that 0 displacement corresponds to the probe being in touch with the sample. Dots represent average over 10 realizations of the experiment, while error bars represent standard deviations.



Fig. 4. The reflected light spectrum for various formaldehyde concentrations (see legend) exhibits an increase of the peak for higher concentrations (a). In (b) the intensity at the peak of the spectrum for various concentrations is plotted, the continuous line represents a guide for the eyes. The y-axes are in arbitrary units.



Fig. 5. Sensor stability: the output voltage is plotted versus time for various formaldehyde concentrations, in (a) the results are shown for the snapper while in (b) for the gouramis fish. The results are taken at zero probe-sample displacement.

increasing the distance between the fiber bundle probe and the sample, at fixed formaldehyde concentration, since more photons get lost through scattering on the fish surface (on the scales) when the probe is distant from the fish itself. This suggests that controlling the probe-sample distance is crucial for consistently comparing measurements of different concentrations. The detector output voltage has been shown for both snapper (Fig. 2(a)) and gouramis fish (Fig. 2(b)) by varying formaldehyde concentrations and probe-sample displacement.

The sensor response is linear with respect to the formaldehyde concentration for both fish samples tested, although the response for different fishes follows different slopes, this is possibly due to different constitution of the two fishes skins. The results are summarized in Fig. 3 where the detector voltage is plotted versus concentration for both fishes at zero displacement of the probe with respect to the sample.

We believe that the increase of reflected optical power for increasing formaldehyde concentration is due to a reduced absorption of red light by the water present in the formalin solution. Indeed increasing formaldehyde concentration in the formalin solution is associated to a decrease of water concentration in the solution itself with a consequent reduction of the absorption.

For consistency, we performed further measurements in order to confirm that the increased concentration of formaldehyde in the formalin solution is indeed responsible for stronger reflection in general and hence to validate the general working principle of our sensor.

We put formalin solution in a transparent glass cuvette and shined the cuvette with a red laser emitting around 637 nm. We measured the spectrum of the reflected radiation for various formaldehyde concentrations by using a Thorlabs CCS200 - Compact Spectrometer with < 2 nm spectral accuracy. By keeping the laser emission power fixed, we indeed observed that more light was reflected for higher formaldehyde concentration. The results of the spectral measurements for various formaldehyde concentrations are plotted in Fig. 4. These findings supports the results shown in Fig. 2.

Our sensor also proves to be very stable. The sensor stability for various formaldehyde concentrations is illustrated in Fig. 5 where we show how the sensor output voltage is stationary in time at fixed concentration.

ſabl	e 1	
------	-----	--

Summary of the	sensor	features.
----------------	--------	-----------

Sensor feature	Snapper fish	Gouramis fish
Sensitivity (mV/%concentration)	1.82	3.31
Linearity (%)	99.89	99.87
Tested range (%)	3–21	3–21
Resolution (%)	0.036	0.031

The sensor features including sensitivity, linearity dynamic range and resolution (defined as the standard deviation of the output voltage variation in time, as depicted in Fig. 5, divided by the sensitivity) are summarized in the following Table 1.

We have furthermore verified that moving the target fish in the x-y plane, at fixed distance from the fiber bundle probe, does not affect the sensor response.

4. Conclusions

In conclusion, we have proposed a novel fiber bundle based sensor to measure the concentration of formaldehyde in fish measuring the reflection of laser light. We observed that the intensity of reflected light increases proportionally to the formaldehyde concentration. The sensor is very stable and responds linearly to the formaldehyde concentration present on the fish surface. Our sensing technique is simple, low cost, it could be applied to detect, in a non invasive and non destructive way, formaldehyde concentration in different food samples, including milk and meat for instance, and it has furthermore the potential to be developed in the future towards a portable device suitable for applications in the field. Future works will include the study of the sensor performances depending on the laser wavelength and also its development towards selectivity in order to identify formaldehyde even in presence of other additional chemicals.

Acknowledgments

The authors acknowledge Prof. S. K. Turitsyn, Dr. A. Gbadebo and Dr. V. Dvoyrin for discussion and support. This work was supported in part by the British Council through Newton-Fund project No. 62292, in part by the Indonesian Government (Fundamental Research Grant, 2019) and by Tahir Professorship Program of the University of Airlangga.

References

- Report of the European Chemicals Agency: https://echa.europa.eu/documents/ 10162/13641/annex_xv_report_formaldehyde_en.pdf/58be2f0a-7ca7-264d-a594da5051a1c74b.
- [2] Report of the United States Environmental Protection Agency: https://www.epa.

gov/sites/production/files/2016-09/documents/formaldehyde.pdf.

- [3] T. Salthammer, S. Mentese, R. Marutzky, Formaldehyde in the indoor environment, Chem. Rev. 110 (2010) 2536–2572.
- [4] Po-Ren Chung, Chun-Ta Tzeng, Ming-Tsun Ke, Chia-Yen Lee, Formaldehyde gas sensors: a review, Sensors 13 (2013) 4468–4484.
- [5] A. Alloucha, M. Guglielminoa, P. Bernhardta, C.A. Serrab, S. Le Calvéa, Transportable, fast and high sensitive near real-time analyzers: Formaldehyde detection, Sens. Actuat. B 181 (2013) 551–558.
- [6] T. Yeh, T. Lin, C. Chen, H. Wen, Analysis of free and bound formaldehyde in squid and squid products by gas chromatography and mass spectrometry, J. Food Drug Anal. 21 (2013) 190–197.
- [7] P. Wahed, Md.A. Razzaq, S. Dharmapuri, M. Corrales, Determination of formaldehyde in food and feed by an in-house validated HPLC method, Food Chem. 202 (2016) 476–483.
- [8] A. De Souza et al., Use of mass spectrometry for the determination of formaldehyde in samples potentially toxic to humans: a brief review, in Mass Spectrometry, M. Aliofkhazraei Editor, IntechOpen, Jun. 2017, ch. 9, pp. 978, Available: https:// www.intechopen.com/books/mass-spectrometry.
- [9] U.S. Aksath, L.S. Selvakumar, M.S. Thakur, Detection of formaldehyde in food samples by enhanced chemiluminescence, Anal. Methods 4 (2012) 699–704.
- [10] O. Bunkoeda, F. Davisc, P. Kanatharanaa, P. Thavarungkula, S.P.J. Higsonc, Sol-gel based sensor for selective formaldehyde determination, Anal. Chim. Acta 659 (2010) 251–257.
- [11] A.A. Gani, M. Yuwono, B. Kuswandi, Development of optical chemical sensor based on pararosaniline in sol-gel matrix for detection of formaldehyde in food samples, Am. J. Anal. Chem. 4 (2013) 661–667.
- [12] K. Wong, J. Deng, X. Wei, S. Shao, D. Xiang, M. Wong, Visual detection of formaldehyde by highly selective fluorophore labeling via gold(III) complex-mediated three-component coupling reaction, Org. Biomol. Chem. 13 (2015) 7408–7411.
- [13] A. Bi, S. Yang, M. Liu, X. Wang, W. Liaob, Fluorescent probes and materials for detecting formaldehyde: from laboratory to indoor for environmental and health monitoring, RSC Adv. 7 (2017) 36421–36432.
- [14] W. Zhoua, H. Dongb, H. Yana, C. Shia, M. Yua, L. Weia, Z. Lia, HCHO-reactive molecule with dual-emission-enhancement property for quantitatively detecting HCHO in near 100% water solution, Sens. Actuat. B 209 (2015) 664–669.
- [15] W. Qu, L. Lu, L. Lin, A. Xu, A silver nanoparticle based surface enhanced resonance Raman scattering (SERRS) probe for the ultrasensitive and selective detection of formaldehyde, Nanoscale 4 (2012) 7358–7361.
- [16] P. Ma, F. Liang, D. Wang, Q. Yang, Y. Ding, Y. Yu, D. Gao, D. Song, X. Wang, Ultrasensitive determination of formaldehyde in environmental waters and food samples after derivatization and using silver nanoparticle assisted SERS, Microchim. Acta 182 (2015) 863–869.
- [17] V. Fauzia, N.C. Imawan, N.M.S. Narayani, A.E. Putri, A localized surface plasmon resonance enhanced dye-based biosensor for formaldehyde detection, Sens. Actuat. B 257 (2018) 1128–1133.
- [18] Z. Zhang, C. Zhao, Y. Ma, G. Li, Rapid analysis of trace volatile formaldehyde in aquatic products by derivatization reaction-based surface enhanced Raman spectroscopy, Analyst 139 (2014) 3614–3621.
- [19] G. Saracoglu, S.E. Hayber, Bent fiber sensor for preservative detection in milk, Sensors 16 (2016) 2094.