PERFORMANCE OF MAGNESIUM HYDROXIDE FLUORIDES AS HETEROGENEOUS ACID CATALYST FOR BIODIESEL PRODUCTION

by Harsasi Setyawati

Submission date: 03-Jan-2023 03:16PM (UTC+0800) Submission ID: 1988145248 File name: mance_of_magnesium_hydroxide_fluorides_as_heterogeneous_acid.pdf (872.32K) Word count: 4141 Character count: 21442



RASAYAN J. Chem. Vol. 11 | No. 1 |312 - 320 | January - March | 2018 ISSN: 0974-1496 | e-ISSN: 0976-0083 | CODEN: RJCABP http://www.rasayanjournal.com http://www.rasayanjournal.co.in

PERFORMANCE OF MAGNESIUM HYDROXIDE FLUORIDES AS HETEROGENEOUS ACID CATALYST FOR BIODIESEL PRODUCTION

S. Indrayanah¹, A. Rosyidah¹, H. Setyawati² and I.K. Murwani^{1*}

¹Jurusan Kimia, Institut Teknologi Sepuluh Nopember, Kampus ITS Sukolilo-Surabaya 60111, Indonesia ²Jurusan Kimia, Universitas Airlangga, Kampus UNAIR JL. Airlangga 4-6 Surabaya 40132, Indonesia. *E-mail : irmina@chem.its.ac.id

ABSTRACT

The magnesium hydroxide fluorides, $MgF_x(OH)_{2,x}$ with different aging temperatures have been synthesized by the sol-gel method. The resulting materials were characterized by various techniques such as XRD, FT-IR, TG/DTG, N₂ adsorption-desorption, pyridine FT-IR and SEM, respectively. The catalytic evaluation of samples was investigated in the simultaneous transesterification and esterification between waste cooking oil (WCO) containing different %FFA and methanol to yield biodiesel. The performance of the catalyst, especially $MgF_x(OH)_{2,x}$ aged at room temperature (RT) showed higher biodiesel yield compared to $MgF_x(OH)_{2,x}$ with increasing of aging temperature. The higher catalytic activity could be attributed to Brønsted acid site, pore diameter size and volume of the materials. Moreover, the yield of biodiesel was not correlated with the surface area of $MgF_x(OH)_{2,x}$. The reusability or lifetime of catalyst decreased after three runs used.

Keywords: MgF_x(OH)_{2-x}, Aging temperature, Heterogeneous acid catalyst, Biodiesel, Waste cooking oil (WCO). © RASÄYAN. All rights reserved

INTRODUCTION

The biodiesel has been considered as alternative energy source for fossil-based fuel. Compared with fossilderived fuel, biodiesel produced by transesterification of triglycerides from vegetable oils or animal fats with short-chained alcohols showed many advantages such as high biodegradability, non-toxicity and renewability. However, the biodiesel obtained from refined vegetable oils or animal fats was uneconomical and impractical because of high raw materials price. In order to reduce the production cost of biodiesel, it is necessary to develop innovative technology using alternative feedstock. Based on the previous research, one of the most attractive alternative raw materials was low-quality oil including waste cooking oil (WCO) due to less expensive. Moreover, the use of WCO will not only reduce the price of biodiesel production, but it will also convert the wastes into resources¹⁻⁶.

Conventionally, the biodiesel obtained from low-quality feedstocks required two processes of reaction. The esterification of high FFA using homogeneous acid catalysts such as H_2SO_4 , H_3PO_4 and HCl was the first step and transesterification reaction of triglycerides in the presence of a base catalysts like NaOH or KOH was the last stage⁷⁻⁸. However, the homogeneous catalyst was not used due to requiring other stages and thus it increased operational cost. Moreover, the catalyst generated much wastewater during product washing, not recoverable and corrosive so that creating other problems to the environment. Therefore, the homogeneous catalyst system for the production of biodiesel became unfavorable.

The use of heterogeneous catalyst system could be used as an alternative. There were many studies to yield biodiesel using heterogeneous base catalysts such as CaO and Dolomite. The processes were cheaper, less corrosive, more environmentally friendly and easily regenerated⁹⁻¹⁰. However, they were not adaptive to free fatty acids (FFA) and water in low-quality oils. Therefore, the heterogeneous acid catalysts became more popular because they were not sensitive to FFA and water contents¹¹. Moreover, they could be used

Rasayan J. Chem., 11(1), 312-320(2018) http://dx.doi.org/10.7324/RJC.2018.1111904

Vol. 11 | No. 1 | 312 - 320 | January - March | 2018

as a catalyst in the simultaneous transesterification and esterification for biodiesel production from lowgrade feedstock in a one step. Some of the heterogeneous acid catalysts have been used to produce biodiesel such as V₂O₅ phosphate¹². Amberlyst-15 and Nafion¹³⁻¹⁴, Zirconium based catalysts¹⁵⁻¹⁶, Heteropoly acids^{17-¹⁸ and Zeolits¹⁹. However, these catalysts showed many disadvantages like the inability to high-temperature reaction (Amberlyst-15 and Nafion), mass transfer limitation and deactivation (Zeolites), loss of activity in polar solvents due to high solubility (Heteropoly acids), high cost (Zirconium) and the easy of being deactivated (V₂O₅ phosphate).}

Currently, there is no study on the production of biodiesel from waste cooking oils (WCO) using magnesium hydroxide fluorides, $MgF_x(OH)_{2-x}$ as a heterogeneous acid catalyst. Therefore, the purpose of this research is to synthesise, characterize and investigate the influence of different aging temperatures of $MgF_x(OH)_{2-x}$ in the simultaneous transesterification and esterification between WCO containing different %FFA and methanol to yield biodiesel. The catalytic activity of the resulting materials, $MgF_x(OH)_{2-x}$ with various aging temperatures is monitored in terms of biodiesel yield obtained from the simultaneous reaction of transesterification and esterification between WCO and methanol in a single stage. Moreover, the durability or lifetime of the catalyst is also evaluated in the optimum conditions of reaction with the same catalyst for production of biodiesel.

EXPERIMENTAL

Chemicals

Mg turnings (98%) was obtained from Aldrich Co. Methanol dry, 48 wt.-% HF, and methanol for HPLC were obtained from Merck Co. Ethanol and acetone were analytically pure or higher and also purchased from Merck Co. The Waste Cooking Oils (WCO) with various %FFA was obtained from Restoran Sederhana, Surabaya, Indonesia.

Preparation of the Catalyst

The samples of $MgF_x(OH)_{2-x}$ (containing a molar ratio of Mg alkoxide to HF = 1:2) with different aging temperatures were prepared by using Mg as a precursor and sol-gel technique. Mg turnings (98%) (31.68 mmol, 0.77 g) was reacted with 50 mL dry methanol for 3 h. Then the amount of 48 wt.-% HF was added and stirred for 3 h. The sol or gel obtained from the previous step was aged at different temperatures i.e room temperature (RT), 65, 100 and 150 °C for 12 h. Furthermore, the solvent was removed under vacuum. Finally, the resulting samples were dried under reduced pressure for 5 h at a temperature of 70 °C.

Characterization of the Catalyst

The phase and structure of samples prepared by sol-gel method were characterized by X-ray diffraction with Cu-K_a radiation source at $\lambda = 1.54056$) and range of 20 about 20-80°. Reflections obtained from this characterization were compared with database of JCPDS-PDF. The chemical bonding and subtitues of materials were recorded with a spectrophotometer FT-IR Shimadzu in the range 4000-400 cm⁻¹ using KBR pellets method. The porosity characteristics of the resulting materials were measured by N₂ adsorptiondesorption using a micromeritics Quantachrome Instruments. The first, the powder was degassed under reduced pressure at a temperature of 70 °C and the surface area of solid was determined using BET method. The thermal analysis of the samples was investigated by TG/DTG apparatus, METTLER TOLEDO with a Pt/PtRh10 thermocouple in N₂ atmosphere. The morphology or topology of the samples was studied using scanning electron microscopy (SEM) (ZEISS EVO MA 10). The surface acidity was determined by FTIRpyridine adsorption method. The pyridine with a purity $\geq 99.5\%$ was supplied by Aldrich Co. The first, the powder (15 mg) was pressed and activated for 3 h under vacuum at 70 °C. After heating to a temperature of 150 °C, the probe is injected during 10 minutes. Furthermore, the spectrum of pyridine adsorbed/desorbed samples were recorded with a spectrophotometer FT-IR Shimadzu in the range from 1300 to 1600 cm⁻¹ with an activated sample as a blank.

Catalytic Test

The catalytic activity of the resulting samples was tested in the simultaneous reaction of transesterification and esterification between waste cooking oils (WCO) and methanol. The reaction of WCO and methanol

MAGNESIUM HYDROXIDE FLUORIDES

Vol. 11 | No. 1 | 312 - 320 | January - March | 2018

in a single step was carried out in a Teflon-lined 200 mL autoclave equipped. The first stage, the reactor was charged with 10 g of WCO and 48 mL methanol (corresponding to the molar ratio of WCO and methanol of 1:30) with 0.5 g catalyst (5% of WCO). Then, the mixtures were heated to 150 °C (oil batch) under constant stirring (600 rpm) for 5 hours. Later, the mixtures were allowed to cool down and the catalyst was separated by centrifugation. The residual methanol was removed with a rotary evaporator and methyl esters, known as biodiesel, was performed with GC chromatography equipped (HP6890) equipped FID detector. Instrument setting: oven (Ramps temperature) = 140 °C, injector temperature = 200 °C and detector temperature = 250 °C.

In this research, information about the stability or durability of catalyst was very important. Therefore, to investigate the reusability of the catalyst, the simultaneous transesterification and esterification between WCO and methanol were performed with the same catalyst and the reaction conditions (WCO to methanol molar ratio of 1:30 at temperature 150 °C for 5 hours under stirring speed 600 rpm with 5 wt.% catalyst). After the reaction finished, mixtures were allowed to cool down and the catalyst was separated by centrifugation. Further the catalyst was separated, washed with ethanol, acetone and distilled water to remove the impurities and used for the subsequent runs.

RESULTS AND DISCUSSION

X-ray diffraction (XRD)

The sol-gel technique has been used for synthesis of MgF_x(OH)_{2-x} with different aging temperatures. In this method, it happens two-step reactions (hydrolysis magnesium as precursor and fluorosis to obtain Mg-F bond²⁰. The structure and phase of MgF_x(OH)_{2-x} with different aging temperatures were characterized by X-ray diffraction. The XRD patterns of MgF_x(OH)_{2-x} with different aging temperatures are summarized in Figure-1. The diffractogram patterns of the resulting samples as shown in Figure-1 shows main peaks at 20 = 27.2°; 40.4°; and 53.5°. These peaks show characteristic peaks of MgF₂(O), which are indexed to the (110), (111) and (211) planes of rutile structure of pure MgF_x(OH)_{2-x} with different aging temperatures. As shown in Figure-1, X-ray diffractogram patterns of MgF_x(OH)_{2-x} with different aging temperatures. As shown in Figure-1, X-ray diffractogram patterns of MgF_x(OH)_{2-x} with different aging temperatures are similar. Based on the results of characterization using X-ray diffraction technique showed that different aging temperatures up to 150° C does not change the structure of MgF_x(OH)_{2-x}.





Fourier-Transform Infrared Spectroscopy (FT-IR)

The materials prepared by sol-gel method with different aging temperatures were also characterized by FT-

MAGNESIUM HYDROXIDE FLUORIDES

Vol. 11 | No. 1 | 312 - 320 | January - March | 2018

IR spectroscopy. The resulting spectra were interpreted to determine of chemical bonding based on its vibrations. The spectra of $MgF_x(OH)_{2-x}$ with different aging temperatures are shown in Figure-2. All samples show broad O-H bands (\blacklozenge) located at 3400-3700 cm⁻¹ that are stretching vibration of water, while the bending vibration of H-O-H and bridged OH group appear about 1640 cm⁻¹(\bullet). The infrared spectra of $MgF_x(OH)_{2-x}$ with different aging temperatures as presented in the Figure-2 exhibit the same vibration at wavenumber about 490 cm⁻¹ (\bullet) which indicate v_{Mg-F} vibration. It is clear that $MgF_x(OH)_{2-x}$ which are synthesized by different aging temperatures does not destroy the structure or chemical bonding of $MgF_x(OH)_{2-x}$ sample, similar to the XRD result.



Fig.-2: FTIR spectra of MgFx(OH)2-x with different aging temperatures: (a) RT, (b) 65, (c) 100 and (d) 150 °C

Thermal Analysis

Thermal analysis of $MgF_x(OH)_{2-x}$ with different aging temperatures was carried out to investigate the thermal stability of materials, especially the influence of different aging temperatures. The TG (A)/DTG (B) curves of the samples are shown in the Fig.-3. The curves of all samples as demonstrated in Fig.-3 show very simple one-step destruction phase at a temperature about 80-300°C that indicate the release of MeOH from Mg(OCH₃)₂·2CH₃OH and loss of the -OH group on the surface of solids. Further both TG (A) and DTG (B) curves as shown in Fig.-3, the decomposition and removal of HF which are appeared at a temperature about 600-700°C is not observed, indicating that the resulting materials are thermally stable. Based on the result, it can be concluded that MgF_x(OH)_{2-x} with different aging temperatures exhibit the same thermal stability.

N₂ Adsorption-Desorption Isotherms

The N₂ adsorption-desorption isotherms of MgF_x(OH)_{2-x} with various aging temperatures are shown in Fig.-4. All samples increase sharply at relatively high pressure, indicating the presence of mesopores. As shown in Figure-4, the adsorption of nitrogen molecules begin to occur in the relative pressure P/P₀ from zero to <0.1. All samples start an interaction in the pore when the pressure reaches from the P/P₀= 0 to P/P₀= 0.9, whereas at higher pressure, P/P₀<1 isothermal curve shape are higher. This result indicated that the adsorption occurs at great pressure. At the moment the pressure is lowered to desorption, the isothermal curve shows a hysteresis loop. This is expected because the adsorption is not the same as the desorption. In addition, hysteretic loop also occurs due to capillary condensation of nitrogen molecules. Through capillary condensation can be obtained information about the type of pores. Based on the IUPAC classification, all materials have typical IV Brunauer isotherm with H1 hysteretic loop, which showed cylindrical pores. Furthermore, the pore diameter size and volume of MgF_x(OH)_{2-x} with different aging

MAGNESIUM HYDROXIDE FLUORIDES

RASĀYAN J. Chem. Vol. 11 | No. 1 |312 - 320 | January - March | 2018

temperatures decreased from 3.63 to 2.67 nm and from 0.1 to 0.089 cc/g after increasing of aging temperatures as shown in Table-1, respectively.



Fig. 4: N_2 adsorption-desorption isotherm of of $MgF_x(OH)_{2-x}$ with different aging temperatures: (a) RT, (b) 65, (c) 100 and (d) 150 °C

This result indicated that the increase in aging temperature can decrease the average pore size and pore

MAGNESIUM HYDROXIDE FLUORIDES

Vol. 11 | No. 1 | 312 - 320 | January - March | 2018

volume of samples. Generally, the specific surface area (BET) of the materials increased with increasing of aging temperatures. Especially for aging temperature of 150 °C, the specific surface area of $MgF_x(OH)_{2-x}$ is 171.88 (m²/g) as shown in Table-1. This indicated that the increase of aging temperatures in the sol-gel method increase the surface area of $MgF_x(OH)_{2-x}$.

Catalysts	$S_{BET}(m^2/g)$	Pore diameter	Pore volume	Acio	l sites
		size (nm)	(nm)	Lewis	Brønsted
				(mmol/g)	(mmol/g)
MgF _x (OH) _{2-x} (RT)	110.97	3.63	0.100	1.458	2.319
MgF _x (OH) _{2-x} (65 °C)	150.55	2.82	0.107	1.549	1.723
MgFx(OH)2-x (100 °C)	148.70	2.40	0.102	1.515	0.717
MgFx(OH)2-x (150 °C)	171.88	2.67	0.089	1.704	0.523

Table-1:	Physicochemical	properties of	catalysts
----------	-----------------	---------------	-----------

Acidity Analysis

The FTIR spectra with pyridine as probe and the values of Lewis/Brønsted acid sites of the resulting materials, $MgF_x(OH)_{2-x}$ are shown in Figure-5 and Table-1. All samples show absorption peaks at 1442-1450 cm⁻¹, indicating the presence of Lewis acid site. In addition, there are peaks at 1540-1550 cm⁻¹, which is characteristic peak of Brønsted acid site. With increase in aging temperatures, the peak of Brønsted acid site decrease. This result indicated that the existence of -OH group decrease with increasing of aging temperatures. The presence of Lewis and Brønsted acid sites in all samples is magnified with a peak at 1490-1500 cm⁻¹.



Fig.-5: FTIR spectra for pyridine adsorption on $MgF_x(OH)_{2-x}$ with different aging temperatures: (a) RT, (b) 65, (c) 100 and (d) 150 °C

SEM Analysis

Study of morphology and topography of the samples was determined by SEM. Figure-6 shows the SEM $MgF_x(OH)_{2-x}$ with different aging temperatures. As shown in Fig.-6, it can be obtained that the morphology of the samples is dissimilar from that of the sample with an increase in aging temperatures. The particle shapes change also from spired to more spherical and homogeneous with an increase in aging temperatures (Figure-6. b-d). However, the particle size of $MgF_x(OH)_{2-x}$ samples are similar, around 0.2-3 µm. Moreover, the aglomerate increases with increasing of aging temperatures as shown in Fig.-6 (a-d).

MAGNESIUM HYDROXIDE FLUORIDES

317

Vol. 11 | No. 1 | 312 - 320 | January - March | 2018

Catalytic Activity

To study the catalytic activity of MgF_x(OH)_{2-x} with different aging temperatures as a heterogeneous acid catalyst, the simultaneous reaction of transesterification and esterification between WCO (containing 4, 7, 10, 13 and 17 %FFA) and methanol to yield biodiesel have been used as a probe reaction. The use of methanol in this reaction was because of more reactive and cheaper than other alcohols. The simultaneous transesterification and esterification were evaluated under the optimum conditions of reaction. Based on the previous experiment, the higher yield of biodiesel resulted from the optimum conditions (oil/methanol molar ratio of 1:30 at a temperature of reaction about 150 °C for 5 hours with catalyst/oil mass ratio of 5% wt. and speed of stirring about 600 rpm). Therefore, these parameter conditions were used, and the results are summarized in Tabel-2. The data are shown in Table-2 demonstrate that the biodiesel yield increases from 26.82% to 38.31, 50.14, 75.29% with increasing of the free fatty acids concentration of waste cooking oils, respectively. However, the yield of biodiesel decreases with increasing of FFA up to 17% (48.45% biodiesel yield). Based on the results, it is concluded that MgF_x(OH)_{2-x} catalyst which aged at room temperature is very adaptive to FFA in waste cooking oil. The presence of acid site, especially Brønsted acid site is believed to improve the biodiesel yield.



Fig.-6: SEM images of MgF_x(OH)_{2-x} with different aging temperatures: (a) RT, (b) 65, (c) 100 and (d) 150 °C

Furthermore, to investigate the effect of different aging temperatures on the $MgF_x(OH)_{2-x}$, the reaction of WCO containing 13% FFA is carried out with optimum reaction condition and the results are presented in Tabel 3. As shown in Tabel 3, the biodiesel yield decreases with increasing of aging temperatures from 75.29% to 62.11, 51.42, 23.89 %, respectively. The higher activity of $MgF_x(OH)_{2-x}$ which aged at room temperature could be correlated with pore diameter size, volume and surface acidity. This result demonstrated that the larger diameter size of pore and volume can absorb more reactants and thus increase its catalytic activity. Moreover, catalyst with a higher total acidity, especially Brønsted acid site is able to capture a large number of FFA in the active site. According to this result, it is clear that the Bronsted acid site is more influence than Lewis acid site in the simultaneous reaction between WCO and methanol in a

MAGNESIUM HYDROXIDE FLUORIDES

Vol. 11 | No. 1 | 312 - 320 | January - March | 2018

single step. On the other hand, although the surface area of $MgF_x(OH)_{2-x}$ with increasing of aging temperature is greater than $MgF_x(OH)_{2-x}$ aged at room temperature, but it can not help improve the contact between WCO and methanol. This shows that the catalytic activity of these samples does not correlate to surface area. The combination of pore diameter and the high surface acidity although the lower surface area is able to provide a high biodiesel production.

Table-2: The effects of FFA (%) on the yield of biodiesel*				
Waste Cooking Oil (WCO)	FFA (%)	Biodiesel yield (%)		
WCO 1	4	26.82		
WCO 2	7	38.31		
WCO 3	10	50.14		
WCO 4	13	75.29		
WCO 5	17	48.45		

*Reaction conditions: WCO/methanol molar ratio 1:30; reaction temperature 150 °C; reaction time 5 h; catalyst amount 5 wt.% of MgF_x(OH)_{2-x} (RT); and stirring speed 600 rpm.

Table-3.	The effects of	different aging	temperatures (of MgF _v (OH) ₂	• on the	vield of biodiesel*
	THE CHICCLO OF	difference digiting	componenter.	OF THE ALCONT/2-	A 011 1110	, ieid of brouteber

Catalysts	Biodiesel yield (%)
MgF _x (OH) _{2-x} (RT)	75.29
MgF _x (OH) _{2-x} (65 °C)	62.11
MgFx(OH) _{2-x} (100 °C)	51.42
dMgFx(OH) _{2-x} (150 °C)	23.89

*Reaction conditions: WCO(13%FFA)/methanol molar ratio 1:30; reaction temperature 150 °C; reaction time 5 h; catalyst amount 5 wt.%; and stirring speed 600 rpm.

The loss of catalyst activity of materials was an important parameter for the heterogeneous catalytic system in simultaneous transesterification and esterification. The reusability of the catalyst is evaluated by the same reaction conditions and $MgF_x(OH)_{2-x}$ aged at room temperature as a catalyst. After each reaction cycles, the used catalyst is recovered by centrifugation and washed with ethanol, acetone and distilled water. The results of the durability of catalysts in simultaneous reactions are displayed in Tabel-4. As summarized in Tabel-4. The yield of biodiesel decreases from 75.29% to 69.23, 51.95% after being used for three runs, respectively. These results show mass loss during the recovery process and the existence of impurities such as fatty acid and byproducts (glycerol), which can cover the pore of the catalyst.

Table-4: Reusability of I	$MgF_{x}(OH)_{2-x}(RT)$ catalyst*
Cycles	Biodiesel yield (%)
1 st use	75.29
2 nd use	69.23
3 rd use	51.95

*Reaction conditions: WCO (13%FFA)/methanol molar ratio 1:30; reaction temperature 150 °C; reaction time 5 h; catalyst amount 5 wt.%; and stirring speed 600 rpm.

CONCLUSION

The magnesium hydroxide fluorides, $MgF_x(OH)_{2-x}$ with different aging temperatures have been successfully obtained from the sol-gel method. Based on the characterization results indicated that all materials showed

MAGNESIUM HYDROXIDE FLUORIDES

319

Vol. 11 | No. 1 | 312 - 320 | January - March | 2018

similar structure, thermal stability, and the particle size. However, the pore diameter size, volume and surface acidity, especially Brønsted acid site decreased with increasing of aging temperatures. Catalytic evaluation in the simultaneous transesterification and esterification reaction between WCO and methanol over the resulting materials as heterogeneous acid catalyst indicated that $MgF_x(OH)_{2-x}$ aged at room temperature (RT) exhibited higher biodiesel yield compared to $MgF_x(OH)_{2-x}$ with an increase in aging temperature. The higher activity of catalyst, $MgF_x(OH)_{2-x}$ aged at room temperature could be attributed to surface acidity, especially Brønsted acid site, pore size and pore volume. Moreover, the durability of the $MgF_x(OH)_{2-x}$ catalyst decreased after three cycles.

ACKNOWLEDGEMENT

The authors thank Directorate of Higher Education (DIKTI) for granting the scholarship and Graduate Research Programe of LPPM-ITS 2017 for financial support.

REFERENCES

- 1. M. Prabhahar, S. Sendilvelan, S. Prakash, M. Saravanakumar, Rasayan J. Chem., 10(4), 1075(2017).
- 2. S. Sendilvelan and K. Bhaskar, Rasayan J. Chem., 10(3), 1043(2017).
- 3. A.T. Kiakalaieh, N.A.S. Amin, H. Mazaheri, Appl. Energ. Rev., 104, 683(2013).
- 4. M. Tariq, S. Ali, N. Khalid, Renew. Sust. Energ. Rev., 16, 6303(2012).
- 5. A.K. Endalew, Y. Kiros, R. Zanzi, Biomass Bioenergy Rev., 35, 3787(2011).
- 6. A.P.S. Chouhan and A.K. Sarma, Renew. Sust. Energ. Rev., 15, 4378(2011).
- 7. M.R. Shahbazi, B. Khoshandam, M. Nasiri, M. Ghazvini, J. Taiwan Inst. Chem. Eng., 43, 504(2012).
- 8. F. Ferella, G.M. Di Celso, I. De Michelis, V. Stanisci, F. Vegliò, Fuel, 89, 36(2010).
- 9. V.G. Deshmane and Y.G Adewuyi, Appl. Catal. A: General, 462, 196(2013).
- 10. R. Olivia, N. Jamarun, S. Arif, Y.A. Sirin, Rasayan J. Chem., 10(1), 160(2017).
- 11. L. Chen, P. Yin, X. Liu, L. Yang, Z. Yu, X. Guo, X. Xin, *Energy*, **36**, 175(2011).
- C. Domingues, M.J.V. Correia, R. Carvalho, C. Henriques, J. Bordado, A.P.S Dias, *Journal Biotechnology*, 164, 433(2013).
- 13. J. Fu, Z. Li, S. Xing, Z. Wang, C. Miao, P. Lv, Z. Yuan, Fuel, 181, 1058(2016).
- 14. Y. Ma, Q. Wang, Z. Gao, X. Sun, N. Wang, R. Niu, H. Ma, Renew. Energ., 86, 643(2016).
- 15. G. Shi, F. Yu, Y. Wang, D. Pan, H. Wang, R. Li, Renew. Energ., 92, 22(2016).
- Y.M. Sani, P.A. Alaba, A.O.R. Yahya, A.R. AbdulAziza, W.M.A.W. Daud, J. Taiwan Inst. Chem. Eng., 59, 195(2016).
- 17. Y.Z. Han, L. Hong, X.Q. Wang, J.Z. Liu, J. Jiaoa, M. Luo, Y. J. Fu, *Industrial Crops and Products*, **89**, 332(2016).
- 18. D.Y. Zhang, M.H. Duan, X.H. Yao, Y.J. Fu, Y.G. Zu, Fuel, 172, 293(2016).
- Y.M Sani, P.A. Alaba, A.O.R. Yahya, A.R. AbdulAziza, W.M.A.W. Daud, J. Taiwan Inst. Chem. Eng., 60, 247(2016).
- 20. S. Wuttke, S.M. Coman, J. Kröhnert, F.C. Jentoft, E. Kemnitz, Catal. Today, 152, 2(2010).

[RJC-1904/2017]

PERFORMANCE OF MAGNESIUM HYDROXIDE FLUORIDES AS HETEROGENEOUS ACID CATALYST FOR BIODIESEL PRODUCTION

ORIGINALITY REPORT

SIMILA	9% ARITY INDEX	10% INTERNET SOURCES	16% PUBLICATIONS	1 % STUDENT PA	PERS
PRIMAR	YSOURCES				
1	S. Indray Murwani hydroxyl active ca effect of Letters, 2 Publication	anah, I.N. Mars . "A facile prepa ated magnesiu talyst for biodie different aging 2018	sih, E. Kemnit aration of m fluorides a esel productio times", Mate	z, I.K. s an on: The rials	3%
2	S Indraya Murwani Heteroge Transest Reaction Science a Publication	anah, Erwin, I N . "Methyl Ester eneous Acid-Ca erification and s", IOP Confere and Engineering	Marsih, Supr Production v talyzed Simul Esterification nce Series: M g, 2017	rapto, l K ia taneous laterials	3%
3	M.S. Kha esterifica pinnata) mesostru molybdo Processii	yoon, B.H. Ham ation of crude k oil to fatty acid uctured SBA-16 phosphoric acion ng Technology,	need. "Single- aranj (Pongar methyl ester supported 12 d catalyst", Fu 2013	step mia s over 2- uel	2%

4	Scholz, G "Local fluorine environments in nanoscopic magnesium hydr(oxide) fluorides studied by ^1^9F MAS NMR", Journal of Fluorine Chemistry, 201112 Publication	1%
5	core.ac.uk Internet Source	1%
6	www.science.gov Internet Source	1%
7	coek.info Internet Source	<1%
8	link.springer.com	<1%
9	www.asianpubs.org	<1%
10	Gudrun Scholz, Christoph Stosiek, Michael Feist, Erhard Kemnitz. "Magnesium Hydroxide Fluorides - New Materials with Adjustable Composition and Properties", European Journal of Inorganic Chemistry, 2012 Publication	< 1 %
11	eprints.utm.my Internet Source	<1%
12	pubs.rsc.org Internet Source	<1%

13	sinta3.ristekdikti.go.id	<1%
14	catalysis.ru Internet Source	<1%
15	Barthos, R "Aromatization of n-heptane on Mo"2C-containing catalysts", Journal of Catalysis, 20051001 Publication	<1%
16	Xiaosong Yang, Xiaoming Li, Jing Liu, Long Rong. "Ni/phosphomolybdic acid immobilized on carbon nanotubes for catalytic cracking of Jatropha oil", Chemical Physics Letters, 2019 Publication	< 1 %
17	docplayer.net Internet Source	<1%
17 18	docplayer.net Internet Source www.orientjchem.org Internet Source	<1 % <1 %
17 18 19	docplayer.netInternet Sourcewww.orientjchem.orgInternet SourceSerrano, D.P "Friedel-Crafts acylation of anisole over hybrid zeolitic-mesostructured materials", Applied Catalysis A, General, 20090515 Publication	<1% <1%

organic framework coated with nickel

hydroxide for energy storage, conversion and detection", Journal of Colloid and Interface Science, 2021

Publication

21	mafiadoc.com Internet Source	<1%
22	myukk.org Internet Source	<1%
23	1library.net Internet Source	<1%
24	Jing Li, Xiaohong Wang, Weimin Zhu, Fenghua Cao. " Zn H PW O Nanotubes with Double Acid Sites as Heterogeneous Catalysts for the Production of Biodiesel from Waste Cooking Oil ", ChemSusChem, 2009 Publication	<1%
25	Pisitpong Intarapong, Sotsanan langthanarat, Pitchaya Phanthong, Apanee Luengnaruemitchai, Samai Jai-In. "Activity and basic properties of KOH/mordenite for transesterification of palm oil", Journal of Energy Chemistry, 2013 Publication	<1%
26	Troncea, S.B "Hydroxylated magnesium fluorides as environmentally friendly catalysts	<1%

fluorides as environmentally friendly catalysts for glycerol acetylation", Applied Catalysis B, Environmental, 20110921 Publication



heterogeneous catalyst in biodiesel production from WCO ", RSC Advances, 2016 Publication

33	V. Sisca, D.A Tanjung, Syukri, Zilfa, N. Jamarun. "CATALYTIC ACTIVITY OF PRECIPITATED CALCIUM CARBONATE FOR BIODIESEL PRODUCTION", Rasayan Journal of Chemistry, 2021 Publication	<1 %
34	asianjournalofchemistry.co.in	<1%
35	notablesdelaciencia.conicet.gov.ar	<1%
36	repository.dl.itc.u-tokyo.ac.jp	<1%
37	Frouri, Fatima, Stéphane Célérier, Philippe Ayrault, and Frédéric Richard. "Inorganic hydroxide fluorides as solid catalysts for acylation of 2-methylfuran by acetic anhydride", Applied Catalysis B Environmental, 2015. Publication	<1 %
38	G. Hendrantoro. "", Antennas and Wireless Propagation Letters, 12/2006 Publication	<1%
39	Oscar A. Anunziata, María L. Martínez. "Sulfated/Zr-containing mesoporous carbons:	<1%

a promising nanostructured catalytic material", Journal of Porous Materials, 2021 Publication

40

Yongming Luo, Zhanqiang Mei, Nengsheng Liu, Hua Wang, Caiyun Han, Sufang He. "Synthesis of mesoporous sulfated zirconia nanoparticles with high surface area and their applies for biodiesel production as effective catalysts", Catalysis Today, 2017 Publication

<1%

<1%



pharmacologyonline.silae.it

Exclude quotes	Off	Exclude matches	Off
Exclude bibliography	On		

PERFORMANCE OF MAGNESIUM HYDROXIDE FLUORIDES AS HETEROGENEOUS ACID CATALYST FOR BIODIESEL PRODUCTION

GRADEMARK REPORT

 FINAL GRADE
 GENERAL COMMENTS

 / O
 Instructor

PAG	GE 1	
PA	GE 2	
PA	GE 3	
PA	GE 4	
PA	GE 5	
PAG	GE 6	
PA	GE 7	
PA	GE 8	
PA	GE 9	