

Journal of Ecological Engineering (JEE) is a peer-reviewed international journal that publishes original research articles in all areas of environmental engineering.

[View more](#)



Current issue

Volume 20, Issue 11, 2019

Coated NPK Fertilizer Based on Citric Acid-Crosslinked Chitosan/Alginate Encapsulant

Vince St D Mesias, Anne Bernadette S. Agu, Precious Japheth L Benablo, Chun-Hu Chen, David Jr P Penaloza

J. Ecol. Eng. 2019; 20(11):1-12

DOI: <https://doi.org/10.12911/22998993/113418>

[Abstract](#)

[Article \(PDF\)](#)

[Stats](#)

Mercury Content in Upper Layers of Soils from the Areas with Various Impacts of Anthropogenic Pressure

Marcin J. Maluszyński, Piotr Dąbrowski, Irena Maluszyńska

J. Ecol. Eng. 2019; 20(11):13-17

DOI: <https://doi.org/10.12911/22998993/113416>

[Abstract](#)

[Article \(PDF\)](#)

[Stats](#)

Biosorption of Heavy Metals from Synthetic Wastewater by Using Macro Algae Collected from Iraqi Marshlands

Shamaa Bahaa, Israa Abdulwahab Al-Baidawi, Safaa Rasheed, Siti Rozaimah Sheikh Abdullah

J. Ecol. Eng. 2019; 20(11):18-22

DOI: <https://doi.org/10.12911/22998993/113415>

[Abstract](#)

[Article \(PDF\)](#)

[Stats](#)

[Submit your paper](#)

[Instructions for Authors](#)

[All issues](#)

[Articles in press](#)



Polish Society
of Ecological Engineering

Most read

[Month](#) [Year](#)

Impact of Municipal Solid Waste Landfill on Environment - a Case Study

Study on the Use and Composition of Bio-Charcoal Briquettes Made of Organic Waste

Assessment of Comprehensive Environmental Pollution Index of Kurichi Industrial Cluster, Coimbatore District, Tamil Nadu, India - a Case Study

Indexes

[Keywords index](#)

[Authors index](#)

Editorial Office and Publisher

Editorial Office:

Lublin University of Technology
Environmental Engineering Faculty
Nadbystrzycka 40B St.
20-618 Lublin
POLAND
e-mail: office@jeeng.net

Publisher:

Polish Society of Ecological Engineering (PTiE)
Branch of PTiE in Lublin
Nadbystrzycka 40B St.
20-618 Lublin
POLAND

Co-publisher:

Scientific Publishing House
Lazurowa 26/1 St.
20-781 Lublin
POLAND

[Submit your paper](#)

[Instructions for Authors](#)

[All issues](#)

[Articles in press](#)

Most read

[Month](#) [Year](#)

[Impact of Municipal Solid Waste Landfill on Environment - a Case Study](#)

[Study on the Use and Composition of Bio-Charcoal Briquettes Made of Organic Waste](#)

[Assessment of Comprehensive Environmental Pollution Index of Kurichi Industrial Cluster, Coimbatore District, Tamil Nadu, India - a Case Study](#)

Indexes

[Keywords index](#)

[Authors index](#)

Editorial Board

EDITOR-IN-CHIEF:

Gabriel Borowski - Lublin University of Technology, Faculty of Environmental Engineering, Poland
e-mail: g.borowski@p.lublin.pl

SCIENTIFIC BOARD MEMBERS:

Maria de Fátima Nunes de Carvalho - Polytechnic Institute of Beja, Portugal
Myroslav S. Malovanyy - Lviv Polytechnic National University, Ukraine
Maria Cristina Lavagnolo - University of Padova, Italy
Antonio Joao Carvalho de Albuquerque - University of Beira Interior, Covilhã, Portugal
Sameh Alsaqoor - Tafila Technical University, Jordan
Süer Anaç - Ege University, Izmir, Turkey
Rune Bakke - University College of Southeast Norway, Norway
Nelson Barros - University of Fernando Pessoa, Porto, Portugal
Zhihong Cao - Institute of Soil Sciences, Chinese Academy of Sciences, Nanjing, China
Aneta Czechowska-Kosacka - Lublin University of Technology, Poland
Magdalena Gajewska - Gdańsk University of Technology, Poland
Joan Garcia - Polytechnic University of Catalonia, Barcelona, Spain
Hassimi Abu Hasan - National University of Malaysia
Faruque Hossain - New York University, New York, USA
Katarzyna Ignatowicz - Białystok University of Technology, Poland
Krzysztof Jóźwiakowski - University of Life Sciences in Lublin, Poland
Aleksander Kiryłuk - Białystok University of Technology, Poland
Michał Kopeć - University of Agriculture in Kraków, Poland
Joanna Kostecka - University of Rzeszów, Poland
Jana Kotovícová - Mendel University in Brno, Czech Republic
Peter Kováčik - Slovak University of Agriculture (SUA) in Nitra, Slovak Republic
Grzegorz Kusza - Opole University, Poland
Fabio Masi - IRIDRA S.r.l., Florence, Italy
Yurij A. Mazhaysky - Ryazan State Agricultural Academy, Ryazan, Russia
Álvaro Monteiro - University of Fernando Pessoa, Porto, Portugal
Adam M. Paruch - Norwegian Institute for Agricultural and Environmental Research - Bioforsk, Norway
Lucjan Pawłowski - Lublin University of Technology, Poland
Ryszard Pokladek - Wrocław University of Environmental and Life Sciences, Poland
Katerina Pozachenyuk - Taurida National V.I. Vernadsky University, Ukraine
Harsha Ratnaweera - Norwegian Institute for Water Research - NIVA, Oslo, Norway
Czesława Rosik-Dulewska - Opole University, Poland
Hynek Roubík - Czech University of Life Sciences Prague, Czech Republic
Pavel Ryant - Mendel University in Brno, Czech Republic
Herald Schöne - Neubrandenburg University of Applied Sciences, Germany
László Simon - University College of Nyíregyháza, Hungary
Elżbieta Skorbilowicz - Białystok University of Technology, Poland
Vladimir Soldatov - National Academy of Sciences of Belarus, Minsk, Belarus
Jung-Jeng Su - National Taiwan University, Taipei, Taiwan
Agata Szymańska-Pulkowska - Wrocław University of Environmental and Life Sciences, Poland
Alexander Tsyganov - Belarusian State Agricultural Academy, Gorki, Belarus
Tomasz Tymliński - Wrocław University of Environmental and Life Sciences, Poland
Sylvia Waara - Halmstad University, Sweden
Andrzej Wac-Włodarczyk - Lublin University of Technology, Poland
Raoul Weiler - University of Leuven, Belgium
Józefa Wiater - Białystok University of Technology, Poland
Barbara Wiśniowska-Kielian - University of Agriculture in Kraków, Poland
Xiaoping Zhu - Hunter College of The City University of New York, USA

CONSULTING EDITORS:

Izolda Gorgol - Department of Applied Mathematics, Lublin University of Technology, Poland
Szymon Obrusiewicz - Faculty of Environmental Engineering, Lublin University of Technology, Poland

Submit your paper

Instructions for Authors

All issues

Articles in press

Most read

Month Year

Impact of Municipal Solid Waste Landfill on Environment - a Case Study

Study on the Use and Composition of Bio-Charcoal Briquettes Made of Organic Waste

Assessment of Comprehensive Environmental Pollution Index of Kurichi Industrial Cluster, Coimbatore District, Tamil Nadu, India - a Case Study

Indexes

Keywords Index

Authors Index



All issues

Volume 20, Issue 6, 2019



Evaluation of Several Biochar Types as Inoculant Carrier for Indigenous Phosphate Solubilizing Microorganism from Acid Sulphate Soil

Nurul Husna, Dedik Budianta, Munandar Munandar, Adipati Napoleon

J. Ecol. Eng. 2019; 20(6):1-8

DOI: <https://doi.org/10.12911/22998993/109078>

[Abstract](#)

[Article \(PDF\)](#)

[Stats](#)

A New Prototype Design and Experimental Study for Assessing Spontaneous Coal Combustion

Aryansyah Aryansyah, Eddy Ibrahim, Subriyer Nasir, Muhammad Said, Ian Kurniawan, Adri Huda

J. Ecol. Eng. 2019; 20(6):9-17

DOI: <https://doi.org/10.12911/22998993/108682>

[Abstract](#)

[Article \(PDF\)](#)

[Stats](#)

Effect of Fuel Combustion Products on Carbon Dioxide Uptake Dynamics of Chlorophyll Synthesizing Microalgae

Vasil Volodymyrovych Dyaehok, Solomiya Mandryk, Victoria Katysheva, Serhiy Huhych

J. Ecol. Eng. 2019; 20(6):18-24

DOI: <https://doi.org/10.12911/22998993/108695>

[Abstract](#)

[Article \(PDF\)](#)

[Stats](#)

Biomethane Emissions: Measurement in Wastewater Pond at Palm Oil Mill by Using TGS2611 Methane Gas Sensor

Ledis Heru Saryono Putro, Dedik Budianta Budianta, Dedi Rohendi Rohendi, Amin Rejo Rejo

J. Ecol. Eng. 2019; 20(6):25-35

DOI: <https://doi.org/10.12911/22998993/108696>

[Abstract](#)

[Article \(PDF\)](#)

[Stats](#)

Utilization of Coal Fly Ash and Oil Palm Empty Fruit Bunch Compost to Improve Uptake of Soil Phosphorus and Yield of Maize Grown on an Ultisol

Fahrurnyah Fahrurnyah, Zaenal Kusuma, Budi Prasetya, Eko Handayanto

J. Ecol. Eng. 2019; 20(6):36-43

DOI: <https://doi.org/10.12911/22998993/108635>

[Abstract](#)

[Article \(PDF\)](#)

[Stats](#)

Minimal Conditions to Degrade Low Density Polyethylene by *Aspergillus terreus* and *niger*

Melina Sáenz, Tamara Borodulina, Linda Díaz, Carlos Banchon

J. Ecol. Eng. 2019; 20(6):44-51

DOI: <https://doi.org/10.12911/22998993/108699>

[Abstract](#)

[Article \(PDF\)](#)

[Stats](#)

Effect of Stormwater System on the Receiver

Roman Babko, Joanna Szulzyk-Cieplak, Yaroslav Danko, Sylwia Duda, Marina Kirichenko-Babko, Grzegorz Łagód

J. Ecol. Eng. 2019; 20(6):52-59

DOI: <https://doi.org/10.12911/22998993/100433>

[Abstract](#)

[Article \(PDF\)](#)

[Stats](#)

Kinetics of Phosphorus Removal From Laundry Wastewater in Constructed Wetlands with *Equisetum hymale*

Febri Eko Wahyudianto, Nur Indradewi Oktavini, Suspto Hariyanto

J. Ecol. Eng. 2019; 20(6):60-65

DOI: <https://doi.org/10.12911/22998993/108919>

[Abstract](#)

[Article \(PDF\)](#)

[Stats](#)

[Submit your paper](#)

[Instructions for Authors](#)

[All issues](#)

[Articles in press](#)

[Most read](#)

[Month](#) [Year](#)

[Impact of Municipal Solid Waste Landfill on Environment - a Case Study](#)

[Study on the Use and Composition of Bio-Charcoal Briquettes Made of Organic Waste](#)

[Assessment of Comprehensive Environmental Pollution Index of Kurichi Industrial Cluster, Coimbatore District, Tamil Nadu, India - a Case Study](#)

[Indexes](#)

[Keywords index](#)

[Authors index](#)

Fish Pass Functionality in Relation to the Dynamics of Hydrological Conditions in the Upper Course of the River Iskar (Case Study)

Silviya Pečkova, Emil Kanev, Ina Dimitrova, Dimitar Kostakov, Eliza Uzunova

J. Ecol. Eng. 2019; 20(6):66-72

DOI: <https://doi.org/10.12911/22998993/108918>

[Abstract](#)

[Article \(PDF\)](#)

[Stats](#)

Effect of the Nile aquifer lithological characteristics on groundwater chemistry in Assiut Governorate, Egypt

Hussein Ali Saleem, Mohamed Ragab El-Tahlawi, Mohamed Abo-Elkassem, Gamal Yehya Boghdadi

J. Ecol. Eng. 2019; 20(6):73-83

DOI: <https://doi.org/10.12911/22998993/108701>

[Abstract](#)

[Article \(PDF\)](#)

[Stats](#)

Reduction of Odor Nuisance from the Composting Process

Monika Gajwa-Widera, Anna Kwarciak-Kozłowska

J. Ecol. Eng. 2019; 20(6):84-89

DOI: <https://doi.org/10.12911/22998993/108688>

[Abstract](#)

[Article \(PDF\)](#)

[Stats](#)

Understanding the Synergic Corrosion Issues with regard to the Water Treatment Station

Renata Katarzyna Włodarczyk, Klaudiusz Majek

J. Ecol. Eng. 2019; 20(6):90-96

DOI: <https://doi.org/10.12911/22998993/108697>

[Abstract](#)

[Article \(PDF\)](#)

[Stats](#)

Biogas Production from Raw Digestate and its Fraction

Wojciech Czekala

J. Ecol. Eng. 2019; 20(6):97-102

DOI: <https://doi.org/10.12911/22998993/108653>

[Abstract](#)

[Article \(PDF\)](#)

[Stats](#)

Identification and Characterization of Potential Feedstock for Biogas Production in South Africa

Nathaniel Sawyer, Cristina Trois, Tilahun Workneh

J. Ecol. Eng. 2019; 20(6):103-116

DOI: <https://doi.org/10.12911/22998993/108652>

[Abstract](#)

[Article \(PDF\)](#)

[Stats](#)

Cellular Automata Markov Method, An Approach for Rice Self-Sufficiency Projection

Dewayany Sutrisno, Wlwin Ambanulan, Irmadi Nahib, Turmuil Turmuil, Jaka Suryanta, Rizka Windastuti, Priyadi Kardono

J. Ecol. Eng. 2019; 20(6):117-125

DOI: <https://doi.org/10.12911/22998993/108651>

[Abstract](#)

[Article \(PDF\)](#)

[Stats](#)

Influence of Water Hardness on the Effectiveness of Coagulation of Humic Compounds

Jadwiga Teresa Kaleta, Alicja Puzkarewicz

J. Ecol. Eng. 2019; 20(6):126-134

DOI: <https://doi.org/10.12911/22998993/108650>

[Abstract](#)

[Article \(PDF\)](#)

[Stats](#)

Assessing the Presence of Heavy Metals in the Area of Giloogoc (Kosovo) by Using Mosses as a Bioindicator for Heavy Metals

Naser Bajraktari, Ilir Morina, Skender Demaku

J. Ecol. Eng. 2019; 20(6):135-140

DOI: <https://doi.org/10.12911/22998993/108639>

[Abstract](#)

[Article \(PDF\)](#)

[Stats](#)

Cavitation-Reagent Technology for Water Purification of Pools and Water Parks

Ivan Aftanazhi, Liliya Shevchuk, Myroslav S. Malovanyy, Letya Strutynska, Igor Samsin

J. Ecol. Eng. 2019; 20(6):141-152

DOI: <https://doi.org/10.12911/22998993/108638>

[Abstract](#)

[Article \(PDF\)](#)

[Stats](#)

A Study of the Smallholder Coffee Agroindustry Sustainability Condition Using the Life Cycle Assessment Approach in Bengkulu Province, Indonesia

Handan Handan, Anas Miftah Fauzi, Meka Syahbana Rusli, Brian Kusadi Rusadi

J. Ecol. Eng. 2019; 20(6):153-160

DOI: <https://doi.org/10.12911/22998993/108636>

[Abstract](#) [Article \(PDF\)](#)

[Stats](#)

Evaluation of the Interaction Among Microalgae *Spirulina* sp, Plastics Polyethylene Terephthalate and Polypropylene in Freshwater Environment

Adlan Khaironi, Sutrisno Anggoro, Sudarno Sudarno

J. Ecol. Eng. 2019; 20(6):161-173

DOI: <https://doi.org/10.12911/22998993/108637>

[Abstract](#) [Article \(PDF\)](#)

[Stats](#)

Evaluation of the Effectiveness of the Coagulation Process in the Treatment of Wastewater from the Foundry Industry

Paulina Dawczak, Marusz Dudzisz

J. Ecol. Eng. 2019; 20(6):174-178

DOI: <https://doi.org/10.12911/22998993/108634>

[Abstract](#) [Article \(PDF\)](#)

[Stats](#)

A Life Factor Approach to the Yield Prediction: a Comparison with a Technological Approach in Reliability and Accuracy

Walter Vlodymyrovych Lyubovyl

J. Ecol. Eng. 2019; 20(6):175-183

DOI: <https://doi.org/10.12911/22998993/108630>

[Abstract](#) [Article \(PDF\)](#)

[Stats](#)

Biosorption of Chromium by Living Cells of *Azotobacter* 58, *Bacillus subtilis* and *Pseudomonas aeruginosa* using Batch System Reactor

Setyo Budi Kurniawan, Muhammad Fauzi Izzati, Isung Fitri Purwati

J. Ecol. Eng. 2019; 20(6):184-189

DOI: <https://doi.org/10.12911/22998993/108629>

[Abstract](#) [Article \(PDF\)](#)

[Stats](#)

The Effect of Foliar Nutrition with Sulphur and Boron, Amino Acids on Morphological Characteristics of Rosette and Wintering Winter Rape (*Brassica napus* L.)

Marek Gugala, Anna Skorska, Krysztyna Zarzecka

J. Ecol. Eng. 2019; 20(6):190-197

DOI: <https://doi.org/10.12911/22998993/108453>

[Abstract](#) [Article \(PDF\)](#)

[Stats](#)

Vulnerability of Rural Areas to Climate Change – Analysis of Similar Units in Terms of Spatial Conditions for Warmińsko-Mazurskie Voivodeship

Katarzyna Kocun-Bera

J. Ecol. Eng. 2019; 20(6):198-208

DOI: <https://doi.org/10.12911/22998993/109454>

[Abstract](#) [Article \(PDF\)](#)

[Stats](#)

Experimental and Theoretical Study for Wind Energy Unit

Hanan Mohammad Abusamah, Farah Dawoud

J. Ecol. Eng. 2019; 20(6):207-214

DOI: <https://doi.org/10.12911/22998993/109459>

[Abstract](#) [Article \(PDF\)](#)

[Stats](#)

Challenges of Soil Resource Protection: A Case Study from Sitnica River Basin (Kosovo)

Valton Bytyqi, Ibrahim Ramadani, Trojaki Agji

J. Ecol. Eng. 2019; 20(6):215-224

DOI: <https://doi.org/10.12911/22998993/109457>

[Abstract](#) [Article \(PDF\)](#)

[Stats](#)

Phenol Biosorption from Polluted Aqueous Solutions by *Ulva lactuca* Alga Using Batch Mode Unit

Mohammed Naeef Abbas, Saadul Mustafa Mohammed Al-Hemroy, Zaidun Najj Abuadi, Thekra Atta Ibrahim

J. Ecol. Eng. 2019; 20(6):225-235

DOI: <https://doi.org/10.12911/22998993/109460>

[Abstract](#) [Article \(PDF\)](#)

[Stats](#)

Implementation of Distributed Hydrological Modeling in a Semi-Arid Mediterranean Catchment "Azzaba, Morocco"

Souadla Abdelmounim, Lahcen Denaabidate, Ismail Boucheu, Mouned Agroyu

J. Ecol. Eng. 2019; 20(6):236-254

DOI: <https://doi.org/10.12911/22998993/109458>

[Abstract](#) [Article \(PDF\)](#)

[Stats](#)

Electrodialytic Recovery of Ammonium and Phosphate Ions in Fertilizer Industry Wastewater by Using a Continuous-Flow Reactor

Deleena Nurul Haniyawah, Arseto Heli Rogotyo, Khas Wismadewanti

J. Ecol. Eng. 2019; 20(6):255-263

DOI: <https://doi.org/10.12911/22998993/109461>

[Abstract](#) [Article \(PDF\)](#)

[Stats](#)

Kinetics of Phosphorus Removal from Laundry Wastewater in Constructed Wetlands with *Equisetum hymale*

Febri Eko Wahyudianto^{1*}, Nur Indradewi Oktavetri¹, Sucipto Hariyanto²

¹ Study Program of Environmental Engineering, Faculty Science and Technology, Universitas Airlangga, Surabaya 60115, Indonesia

² Study Program of Biology, Faculty Science and Technology, Universitas Airlangga, Surabaya 60115, Indonesia

* Corresponding author's e-mail: febri.eko.w@fst.unair.ac.id

ABSTRACT

The objective of this study was to determine the capacity, process, and kinetics of phosphorus (PO₄-P) nutrients pollutant removal in constructed wetlands with *Equisetum hymale* plants. This research was conducted by using a batch system constructed wetlands with detention time variation of 1–5 days and using gravel, sand, and soil as the media. The laundry wastewater used for this research was collected from commercial activity in Surabaya city. The results of this research showed that the removal efficiency of PO₄-P using the constructed wetlands with *Equisetum hymale* was between the range of 95.49–99.43%. The removal process was done by screening-adsorption, and the sedimentation mechanisms from the media, and the biosorption by the plants was shown by the increasing content of PO₄-P in soil and plants, which amounted to 14.80% and 9.23% respectively. The removal kinetics of PO₄-P was according to the second-order model with value of R² = 0.99.

Keywords: constructed wetlands, kinetics, *Equisetum hymale*

INTRODUCTION

The issues in water pollution are caused not only by the amount of hazardous contents intake in the water but can also be caused by the nutrient pollutants that percolate into the water source. Phosphorus is one of the nutrients that could pollute the water in environment to the greatest extent, that could cause eutrophication in the water sources (Le Moal et al., 2019). The phosphorus contents that infiltrate into the water could be categorized as point source or non-point source. The example of phosphorus source that come from point source are the effluent of industrial or laundry and domestic activities, while non-point phosphorus sources could be found in the phosphorus diffusion process in agricultural activities (Di Luca et al., 2017; Vymazal, 2014). At present, laundry and domestic activities are the main phosphorus producers, especially in large cities in Indonesia because of the increasing population and few wastewater treatment plants.

The laundry and domestic wastewater need to be treated by reducing the nutrient which got into the water source. One of the efforts to treat laundry wastewater is by using the constructed wetlands concept (Vymazal, 2014). Constructed wetlands have a few benefits which are the low operational costs, easy and feasible operation, contribution to the improvement of the landscape aesthetics, and providing habitat for many other organisms (Meng et al., 2014; Yeh et al., 2015; Zhang et al., 2014; Józwiakowski et al., 2018). Those benefits could justify the application of constructed wetlands for treating laundry wastewater in populous areas.

There are many other studies related to the use of constructed wetlands for treating wastewater, which aim at determining the compatible and suitable plants species for constructed wetlands unit. For example, the *Typha*, *Phragmites australis*, and *Scirpus* species can be used in treating domestic wastewater (Timotewos et al., 2017). On other hand, there are many factors that could

affect the process in constructed wetlands, such as the substrate type, substrate capacity, hydraulic load and retention time, water depth, and feeding mode in constructed wetlands (Meng et al., 2014; Sirianuntapiboon et al., 2006; Wu et al., 2015). Therefore, the aim of this research was to determine the capacity, process, and kinetics of phosphorus ($\text{PO}_4\text{-P}$) nutrients removal in constructed wetlands with *Equisetum hymale* plants.

MATERIAL AND METHODS

Constructed wetlands reactors

The constructed wetlands reactors consist of 10 reactors with variation of 5 different hydraulic retention times (each variation with 2 replications). The reactors were made of pots with length, width, and height of 80 cm, 20 cm, and 25 cm respectively, and the volume of 40 liters. The media composition in the constructed wetlands reactors consisted of gravel (ϕ 20 mm), sand (ϕ 0.4–2 mm), and soil with the height of each media amounting to 3 cm, 3 cm, and 15 cm, respectively. Each reactor consisted of 4 groups (each group comprised 150 plants) of *Equisetum hymale* plants, which was obtained from a nursery in East Java. The scheme of constructed wetlands is shown in Figure 1. The sampling point in this reactor was located 2.5 cm from the bottom of reactor and the water level was about 3 cm above media. The laundry wastewater used for this research was collected from commercial laundry in Surabaya city with characteristics shown in Table 1. The constructed wetlands reactors were placed inside a greenhouse available in Biology Department, Universitas Airlangga under normal conditions, without any lightning control.

Sampling and analysis

The samples were taken every day for 5 days, continuously, in a glass container and kept inside the cold-storage box at a temperature of 4°C before the analysis. The samples taken were analyzed for the $\text{PO}_4\text{-P}$ content with chloride Stannous method which referred to the standard methods for examination of water and waste water 4500-P D (APHA, 2012) using spectrophotometer (Broco). Soil, plant's stems and roots used in this research were taken as random samples on day 5 to be analyzed for phosphorus content. The soil, stems, and roots were dried using an oven (Memmert, Germany) at a temperature of 105°C for 24 hours until the constant mass was achieved. The phosphorus content in soil and plants (mg/kg) was analyzed using P.Olsen method. The calculation of removal percentage could be calculated with the equation (1) (Olguín et al., 2017):

$$\text{Removal}(\%) = \frac{\text{Inletconcentration} - \text{Outletconcentration}}{\text{Inletconcentration}} \times 100\% \quad (1)$$

Batch kinetics experiment

Acclimatization of *Equisetum hymale* plants was conducted for 7 days after planting using tap water. The day after acclimatization, the water was drained to be replaced with the laundry wastewater until the media were submerged in the wastewater to about 3 cm above media. The kinetics attempt was conducted using batch method with retention time of 1, 2, 3, 4, and 5 days for each constructed wetland unit. First-order and second-order pollutant model equations could be used to find the kinetics model in the constructed wetlands with *Equisetum hymale* which was expressed in equation 2 and 3 (Farzadkia et al., 2015).




Figure 1. Constructed wetlands reactor

Table 1. Characteristic of laundry waste water

Parameters	Concentration	Effluent Standart*
Temperature (°C)	29–31	-
pH	6.9–7.6	6–9
Phospat	10.067	10
COD	861.54	250
TSS	1040	100
Surfactan Anionic	78.13	10

* Regulation Governor East Java Indonesia No. 72/2013 concerning Waste Water Quality of Industry.

$$\frac{S_i - S_e}{HRT} = k_1 S_e \quad (2)$$

According to the equation (2) S_i is the influent concentration (mg/L), S_e is the effluent concentration (mg/L), HRT is the retention time (day), and k_1 is the first-order kinetics coefficient.

$$\frac{HRT}{E} = n \times HRT + m \quad (3)$$

According to the equation (3) E is the value of $S_i - S_e / S_i$ and n and m are the coefficients in which second-order coefficient (ks) is equal to $S_i / m \times X$.

RESULT AND DISCUSSION

Nutrients removal capacity and process

The phosphorus removal capacity in constructed wetlands with *Equisetum hymale* was calculated with equation (1) by comparing the value between the initial concentration value and final

concentration value in each reactor with variation of retention time. The result of removal capacity analysis is as shown in Figure 2. The initial concentration value of $PO_4\text{-P}$ (Si) in laundry wastewater used in this research 10.067 mg/L. The wastewater treatment using *Equisetum hymale* in constructed wetlands could decrease the $PO_4\text{-P}$ final concentration (Se) to 0.049–0.454 mg/L with the removal efficiency up to 95.49–99.51%.

The results in Figure 2 showed that the highest $PO_4\text{-P}$ removal capacity was at retention time of day 4, which was up to 99.51%. This value showed a higher result than one in the research by Di Luca (2017), in which the constructed wetlands could decrease phosphorus content to 70.5%. Constructed wetlands could reduce total phosphorus as well up to 79,5% in the case of treating artificial domestic wastewater (Gupta et al., 2016). By using green rooftop water recycling system, constructed wetlands could even reduce phosphorus to the maximum degree up to 92% (Ramprasad et al., 2017). The removal of $PO_4\text{-P}$ in constructed wetlands was affected by the retention time of waste water treatment as well (Olguin et al., 2017; Wu et al., 2015). The results from this research showed that longer retention time could increase the removal capacity. The results obtained corresponded to the prior research that had been conducted, which related to the influence of detention time in which 4 days retention time did not only contribute to the maximum removal capacity but also could keep the removal capacity stable (Ghosh and Gopal, 2010).

The phosphorus nutrients removal process from laundry wastewater using constructed wetlands with *Equisetum hymale* was involved a few components that were found in the reactor, which




Figure 2. Removal capacity of phosphorus ($PO_4\text{-P}$) from constructed wetlands with *Equisetum hymale*

included the soil media and plants. The analysis results from the media and plants in constructed wetlands were expressed in Table 2. The table showed that the increase of the phosphorus content occurred in the soil and plants, both below the ground part such as the roots and the surface part such as the stems. The highest phosphorus concentration was shown in the stems of *Equisetum hymale* which was 15.35%; in soil was 14.80%; while in roots was 9.23%.

The phosphorus removal process that occurred in the plants and soil showed that the phosphorus in the laundry wastewater could be taken up by *Equisetum hymale*. Phosphorus itself is one of the macro-nutrients that is needed for the plants to support their growth (Abdolzadeh et al., 2010). Plants could adsorb PO_4 -P that came from a dilution soaked into the soil through their roots by the diffusion mechanism (Smith, 2002). In turn, the PO_4 -P removal that occurred in the constructed wetlands media, especially in the soil, could happen because of a few factors such as the bonds with organic matters and the media's alkalinity condition (Di Luca et al., 2017). Beside all those factors, the phosphorus removal in media was also possible because of adsorption process

and sedimentation that occurred in constructed wetlands media (Merino-Solís et al., 2015). Therefore, constructed wetlands with *Equisetum hymale* could remove phosphorus by absorption, adsorption, and sedimentation mechanisms in the plants and media.

Kinetics model

In this kinetics study, two models used were first-order kinetic and second-order kinetic (grove model) models which are described in equation (2) and (3) (Farzadkia et al., 2015). Those two models were used to determine the tendency process that occurred in constructed wetlands with *Equisetum hymale* in reducing the PO_4 -P content from laundry wastewater. The results of models from the batch experiment in constructed wetlands with *Equisetum hymale* were expressed in Figures 3 and 4. In Figure 3, the kinetics model from PO_4 -P removal indicated the correlation between effluent concentration value (Se) and concentration reduction value (Si-Se) for each variation time (HRT). The results showed that the linear regression $y = 16.819x + 1.8922$ with regression coefficient (R^2) was 0.8569. In turn, in Figure 4, the second-order kinetic (grove model) gave linear regression of $y = 1.0017x + 0.0268$ with regression coefficient (R^2) of 0.9999. With the results obtained, it could be determined that the PO_4 -P removal process which occurred in constructed wetlands with *Equisetum hymale* had tendencies towards the second-order kinetic model. It indicated that the process was done chemically. The mechanism that occurred in PO_4 -P removal in other studies indicated that phosphorus removal referred to the

Table 2. Phosphorus accumulation analysis in soil and plants

Parameter(s)	Unit	Before	After	Accumulation (%)
Soil	mg/kg	9.39	10.78	14.80
Plant (Above ground)	mg/kg	38.81	44.73	15.25
Plant (Below ground)	mg/kg	220.98	241.37	9.23




Figure 3. The first-order kinetic model




Figure 4. The second-order kinetic model (grove model)

second-order kinetic as well (Pérez et al., 2014). The second-order kinetic model could also be applied to the ammonium nitrogen removal using constructed wetlands (Zhu et al., 2011) and 17α -methyltestosterone removal with *Salvinia cucullata* (Adnan and Thanasupsin, 2016).

CONCLUSIONS

Constructed wetlands with *Equisetum hymale* could reduce the nutrients pollutant in the form of $\text{PO}_4\text{-P}$ with the removal efficiency of up to 95.49–99.43%. The considered process involved screening-adsorption, sedimentation, and biosorption in *Equisetum hymale* plants and occurred by referring to the second-order kinetic model ($R^2 > 0.9999$).

Acknowledgements

This study was supported by Faculty of Science and Technology, Universitas Airlangga.

REFERENCES

- Abdolzadeh, A., Wang, X., Veneklaas, E.J., Lambers, H., 2010. Effects of phosphorus supply on growth, phosphate concentration and cluster-root formation in three *Lupinus* species. *Annals of Botany*. vol. 105, 365–374.
- Adnan, F., Thanasupsin, S.P., 2016. Kinetic studies using a linear regression analysis for a sorption phenomenon of 17α -methyltestosterone by *Salvinia cucullata* in an active plant reactor. *Environmental Engineering Research*. vol. 21, 384–392.
- APHA, 2012. *Standard Methods for the Examination of Water and Wastewater*, 21th ed. American Public Health Association, Washington DC, USA.
- Di Luca, G.A., Maine, M.A., Mufarrege, M.M., Hadad, H.R., Pedro, M.C., Sánchez, G.C., Cafaratti, S.E., 2017. Phosphorus distribution pattern in sediments of natural and constructed wetlands. *Ecological Engineering*. vol. 108, 227–233.
- Farzadkia, M., Ehrampush, M.H., Mehrizi, E.A., Sadeghi, S., Talebi, P., Salehi, A., Kermani, M., 2015. Investigating the efficiency and kinetic coefficients of nutrient removal in the subsurface artificial wetland of Yazd wastewater treatment plant. *Environmental Health Engineering and Management Journal*. vol. 2, 23–30.
- Ghosh, D., Gopal, B., 2010. Effect of hydraulic retention time on the treatment of secondary effluent in a subsurface flow constructed wetland. *Ecological Engineering*. vol. 36, 1044–1051.
- Gupta, P., Ann, T.W., Lee, S.M., 2016. Use of biochar to enhance constructed wetland performance in wastewater reclamation. *Environmental Engineering Research*. vol. 21, 36–44.
- Józwiakowski K., Bugajski P., Kurek K., de Carvalho M., Almeida M.A., Gajewska M., Siwiec T., Borowski G., Czekala W., Dach J., Gajewska M. 2018. The efficiency and technological reliability of biogenic compounds removal during long-term operation of a one-stage subsurface horizontal flow constructed wetland. *Separation and Purification Technology*. vol. 202, 216–226.
- Le Moal, M., Gascuel-Oudoux, C., Ménesguen, A., Souchon, Y., Étrillard, C., Levain, A., Moatar, F., Pannard, A., Souchu, P., Lefebvre, A., Pinay, G., 2019. Eutrophication: A new wine in an old bottle? *Science of The Total Environment*. vol. 651, 1–11.
- Meng, P., Pei, H., Hu, W., Shao, Y., Li, Z., 2014. How to increase microbial degradation in constructed wetlands: Influencing factors and im-

- provement measures. *Bioresource Technology*. vol 157, 316–326.
11. Merino-Solis, M., Villegas, E., de Anda, J., López-López, A., 2015. The Effect of the Hydraulic Retention Time on the Performance of an Ecological Wastewater Treatment System: An Anaerobic Filter with a Constructed Wetland. *Water*. vol. 7, 1149–1163.
 12. Olguín, E.J., Sánchez-Galván, G., Melo, F.J., Hernández, V.J., González-Portela, R.E., 2017. Long-term assessment at field scale of Floating Treatment Wetlands for improvement of water quality and provision of ecosystem services in a eutrophic urban pond. *Science of The Total Environ*. vol. 584–585, 561–571.
 13. Pérez, M.M., Hernández, J.M., Bossens, J., Jiménez, T., Rosa, E., Tack, F., 2014. Vertical flow constructed wetlands: Kinetics of nutrient and organic matter removal. *Water Science and Technology*. vol. 70, 76–81.
 14. Ramprasad, C., Smith, C.S., Memon, F.A., Philip, L., 2017. Removal of chemical and microbial contaminants from greywater using a novel constructed wetland: GROW. *Ecological Engineering*. vol. 106, 55–65.
 15. Sirianuntapiboon, S., Kongchum, M., Jitmaikasem, W., 2006. Effects of hydraulic retention time and media of constructed wetland for treatment of domestic wastewater. *Journal of Agricultural Research*. vol. 1, 27–37.
 16. Smith, F.W., 2002. The phosphate uptake mechanism. *Plant and Soil*. vol. 245, 105–114.
 17. Timotewos, M.T., Kassa, K., Reddythota, D., 2017. Selection of mesocosm to remove nutrients with constructed wetlands. *Journal of Ecological Engineering*. vol. 18, 42–51.
 18. Vymazal, J., 2014. Constructed wetlands for treatment of industrial wastewaters: A review. *Ecological Engineering*. vol. 73, 724–751.
 19. Wu, H., Zhang, J., Ngo, H.H., Guo, W., Hu, Z., Liang, S., Fan, J., Liu, H., 2015. A review on the sustainability of constructed wetlands for wastewater treatment: Design and operation. *Bioresource Technology*. vol. 175, 594–601.
 20. Yeh, N., Yeh, P., Chang, Y.H., 2015. Artificial floating islands for environmental improvement. *Renewable and Sustainable Energy Reviews*. vol. 47, 616–622.
 21. Zhang, D.Q., Jinadasa, K.B.S.N., Gersberg, R.M., Liu, Y., Ng, W.J., Tan, S.K., 2014. Application of constructed wetlands for wastewater treatment in developing countries – A review of recent developments (2000–2013). *Journal of Environmental Management*. vol. 141, 116–131.
 22. Zhu, W.L., Cui, L.H., Ouyang, Y., Long, C.F., Tang, X.D., 2011. Kinetic Adsorption of Ammonium Nitrogen by Substrate Materials for Constructed Wetlands. *Pedosphere*. vol.21, 454–463.

Journal of Ecological Engineering

Country [Poland](#) -  [SJR Ranking of Poland](#)

Subject Area and Category [Agricultural and Biological Sciences](#)
[Ecology, Evolution, Behavior and Systematics](#)
[Environmental Science](#)
[Environmental Science \(miscellaneous\)](#)

Publisher [Polskie Towarzystwo Inżynierii Ekologicznej](#)

Publication type [Journals](#)

ISSN [22968992](#)

Coverage [2013-ongoing](#)

10

H Index

Scope - Industrial and municipal waste management - Pro-ecological technologies and products - Energy-saving technologies - Environmental landscaping - Environmental monitoring - Climate change in the environment - Sustainable development - Processing and usage of mineral resources - Recovery of valuable materials and fuels - Surface water and groundwater management - Water and wastewater treatment - Smog and air pollution prevention - Protection and reclamation of soils - Reclamation and revitalization of degraded areas - Heavy metals in the environment - Renewable energy technologies - Environmental protection of rural areas - Restoration and protection of urban environment - Prevention of noise in the environment - Environmental life-cycle assessment (LCA) - Simulations and computer modeling for the environment

- [Homepage](#)
- [How to publish in this journal](#)
- [Contact](#)
- [Join the conversation about this journal](#)

